

F6.30.XX

Paddlewheel Flow Transmitter



| Κωδικός Προϊόντος | tooltiplmage | Version | Power supply | Lenght | Main Wetted Materials | Enclosure | Flow Rate Range | Weight (gr.) |
|-------------------|--------------|---------|--------------|--------|-----------------------|-----------|---------------------|--------------|
| F6.50.01 | - | Hall | 12 - 24 VCC | L0 | C-PVC \$ EPDM | IP65 | From 0,15 to 8 m/s* | 750 |
| F6.50.02 | - | Hall | 12 - 24 VCC | L0 | C-PVC \$ FKM | IP65 | From 0,15 to 8 m/s* | 750 |
| F6.50.03 | - | Hall | 12 - 24 VCC | L1 | C-PVC \$ EPDM | IP65 | From 0,15 to 8 m/s* | 800 |
| F6.50.04 | - | Hall | 12 - 24 VCC | L1 | C-PVC \$ FKM | IP65 | From 0,15 to 8 m/s* | 800 |
| F6.50.05 | - | Hall | 12 - 24 VCC | L0 | PVDF \$ EPDM | IP65 | From 0,15 to 8 m/s* | 750 |
| F6.50.06 | - | Hall | 12 - 24 VCC | L0 | PVDF \$ FKM | IP65 | From 0,15 to 8 m/s* | 750 |
| F6.50.07 | - | Hall | 12 - 24 VCC | L1 | PVDF \$ EPDM | IP65 | From 0,15 to 8 m/s* | 800 |
| F6.50.08 | - | Hall | 12 - 24 VCC | L1 | PVDF \$ FKM | IP65 | From 0,15 to 8 m/s* | 800 |
| F6.50.09 | - | Hall | 12 - 24 VCC | L0 | 316L SS \$ EPDM | IP65 | From 0,15 to 8 m/s* | 950 |
| F6.50.10 | - | Hall | 12 - 24 VCC | L0 | 316L SS \$ FKM | IP65 | From 0,15 to 8 m/s* | 950 |
| F6.50.11 | - | Hall | 12 - 24 VCC | L1 | 316L SS \$ EPDM | IP65 | From 0,15 to 8 m/s* | 1000 |
| F6.50.12 | - | Hall | 12 - 24 VCC | L1 | 316L SS \$ FKM | IP65 | From 0,15 to 8 m/s* | 1000 |



F6.30.XX

- APPLICATIONS β Industrial water and wastewater treatment β Cooling water systems β Swimming pools β Flow control and monitoring β Water treatment β Water regeneration plant β Processing and manufacturing industry β Water distribution MAIN FEATURES β High chemical resistance β Pipe size range: from DN15 (0,5β) to DN600 (24β) β Low pressure drop β Friendly calibration procedure β 4-20 mA, frequency or volumetric pulse output settable by USB β SSR settable as alarm by laptop