

## FWSG SE

### Εύστρα για άκρα σωλήνων και περιοχές σέλας d 63 – d 315

Dimension-bound scraper tool for the reliable removal of the oxide layer of HDPE and PE-Xa pipe ends and in the saddle area. Scraper blade designed as turning blade with 2 blades (twice the service life). Easy clamping thanks to the open design of the scraper tool. The tool is delivered in a transport box.



Κωδικός προϊόντος	Article description	Diameter Area	BX	PU	Weight kg
613562	FWSG SE 63	d 63	1	40	4,100
613563	FWSG SE 75	d 75	1	30	4,300
613564	FWSG SE 90	d 90	1	30	4,600
613565	FWSG SE 110	d 110	1	40	4,600
613566	FWSG SE 125	d 125	1	40	4,600
613567	FWSG SE 140	d 140	1	30	4,900
613568	FWSG SE 160	d 160	1	30	4,900
613569	FWSG SE 180	d 180	1	30	5,100
613570	FWSG SE 200	d 200	1	30	5,600
613571	FWSG SE 225	d 225	1	30	5,600
613572	FWSG SE 250	d 250	1	30	8,200
613573	FWSG SE 280	d 280	1	30	8,200
613574	FWSG SE 315	d 315	1	30	8,200

## FWSG SE

### Εύστρα για άκρα σωλήνων και περιοχές σέλας d 63 – d 315

#### Application

FRIATOOLS scraper tools for the perfect preparation of HDPE pipe surfaces: Consistently uniform removal of oxide layers for the perfect electrofusion.

#### The crucial difference

Having the correct tools to perform installation on site makes all the difference. We see ourselves as specialists in the electrofusion of HDPE piping systems, so our development work has also included equipment and accessories for your needs from the very outset.

We know exactly what matters and what is needed in the field, and we can offer you a range of equipment tailored to the daily challenges encountered on the building site:

FRIATOOLS scraper tools for all pipe diameters and for a wide range of scrape lengths and saddle surfaces. These safeguard a uniform removal of material and reproducible quality for the optimal processing and reliable fusion of HDPE pipes.

Put your trust in tools that produce the perfect results.

#### Good reasons for the FRIATOOLS scraper tools FWSG SE:

Safe and reliable removal of oxide layers on PE 80, PE 100, and PE-X pipes

Reliable scraping of surface areas of saddle parts on the pipe as well as preparing a fitting fusion on the pipe end

Spring-loaded and moveable blade support to balance out uneven and bendy pipes

Simple clamping due to open construction design

Three grips allow for simple and effort saving turning on the pipe

Robust and compact design

Simple handling

Scraper blade designed as turning blade with 2 cutting edges (twice the service life)

Delivery in practical aluminum transport case