

STRAUB-FLEX-4

All pipe materials can be reliably connected with STRAUB-FLEX couplings. STRAUB-FLEX pipe couplings enable pipe connections for practically all conceivable pipe diameters, for the same or different types of pipe materials, various media and temperatures as well as for a wide range of the operating pressure values. The sealing sleeve separates the coupling casing from the pipe surface so that sound, vibrations and oscillations are optimally damped.



FLEX 4 ø 323.9 - 812.8 mm

adMm	Clamping range [mm]	PN Industry [bar] 25	PN Industry [bar] 6	PN Industry [bar] 10	PN Industry [bar] 16	PN Industry [bar] 20	PN Industry [bar] 2.5
323.9	320 - 327	W1 W5	W1 W5	W1 W5	W1 W5	W1 W5	W1 W5
355.6	352 - 359	W1 W5	W1 W5	W1 W5	W1 W5	W1 W5	W1 W5
406.4	403 - 409	W1 W5	W1 W5	W1 W5	W1 W5	W1 W5	W1 W5
457.2	454 - 460	W1 W5	W1 W5	W1 W5	W1 W5	W1 W5	W1 W5
508	505 - 512	W1 W5	W1 W5	W1 W5	W1 W5	W1 W5	W1 W5*
558.8	555 - 562	W1 W5	W1 W5	W1 W5	W1 W5	W1 W5	W5*
609.6	606 - 613	W1 W5	W1 W5	W1 W5	W1 W5	W1 W5	W5*
655	652 - 658	W1 W5	W1 W5	W1 W5	W1 W5	W5*	W5*
711.2	707 - 715	W1 W5	W1 W5	W1 W5	W1 W5	W5*	W5*
762	758 - 766	W1 W5	W1 W5	W1 W5	W1 W5	W5*	W5*
812.8	809 - 817	W1 W5	W1 W5	W1 W5	W1 W5	W5*	W5*