


FCIV-PVC-T+magnet

Float: PP (Polypropylene) red + Magnet



Κωδικός Προϊόντος	tooltiplmage	d	Flow rate range for \$ HCl 30 - 33% [l/h]	B	E	C
FCIV016T2M0014M	-	16	1,4 - 14	199	165	171
FCIV016T2M0018M	-	16	2 - 18	199	165	171
FCIV016T2M0045M	-	16	5 - 45	199	165	171
FCIV016T2M0090M	-	16	10 - 90	199	165	171
FCIV016T2M0140M	-	16	14 - 140	199	165	171
FCIV020T2M0023M	-	20	2 - 23	208	170	176
FCIV020T2M0045M	-	20	5 - 45	208	170	176
FCIV020T2M0090M	-	20	10 - 90	208	170	176
FCIV020T2M0140M	-	20	14 - 140	208	170	176
FCIV020T2M0185M	-	20	19 - 185	208	170	176
FCIV020T2M0300M	-	20	30 - 300	208	170	176
FCIV025T2M0075M	-	25	7,5 - 75	229	185	191
FCIV025T2M0140M	-	25	14 - 140	229	185	191
FCIV025T2M0185M	-	25	19 - 185	229	185	191
FCIV025T2M0325M	-	25	30 - 325	229	185	191
FCIV025T2M0600M	-	25	45 - 600	229	185	191
FCIV032T2M0185M	-	32	19 - 185	250	200	206
FCIV032T2M0280M	-	32	28 - 280	250	200	206
FCIV032T2M0550M	-	32	55 - 550	250	200	206
FCIV032T2M0900M	-	32	90 - 900	250	200	206

FCIV-PVC-T+magnet

- Metering tubes are available in Trogamid (PA) suitable for most inert media, PVC-U suitable for slight corrosive media and Polysulfone (PSU) suitable for corrosive media on an extended operating temperature range. End connectors available in PVC-U, PVC-C, PP, SS, Malleable Cast Iron. Male threads moulded onto the end of the metering tube are used for easy mounting of unions. Standard unions are in PVC-U but others are available according to the different working conditions; Metal unions widen the range of operating conditions such as pressure and temperature. The floats are available in Stainless Steel AISI 316 and in PP to match the proper chemical compatibility with the flow medium and to offer different measuring ranges. Magnetic Float option is available to be combined with micro switches for MIN and MAX alarm, clamped on the guide of the flowmeter. The micro switches, housing a bistable reed contact are activated by the passage of the magnet incorporated into the float. Flowmeters body are equipped with a double guide allowing the installation of two alarm in a very close position. Double scale option available for specific application requirements to customize measuring units for an easy conversion or comprehension of the flow rate values.
- β' Wide choice of measuring scales: water scale from 1,5 to 50.000 l/h, HCl scale from 1,4 to 23.000 l/h, NaOH 30% scale from 0,25 to 43.000 l/h, NaOH 50% scale from 0,025 to 40.000 l/h, Air scale from 0,025 to 500 Nm³/h β' Wide choice of end connections available in PVC-U, PVC-C, PP-H, AISI 316 SS, Carbon Steel β' Eight different diameters β' Three different plastic tube materials: PA, PVC and PSU β' Float materials available in SS and PP, with or without magnet β' High level of accuracy: FS accuracy class 2,5; FC accuracy class 4 β' Simple operation and very limited maintenance. β' Other engineering units like LPM, m³/h or % together with double scales and special scales are available on request.