

HF6.XXX

PVDF Body Level/Pressure Hydrostatic Transmitter



| Κωδικός προϊόντος | tooltiplmage | Operative Range | Process connection | Main Wetted Materials | Measuring Mode | Diaphragm | Cable | Weight (gr.) (g) |
|-------------------|--------------|-----------------|--|----------------------------------|-------------------|--------------------------|---------|------------------|
| HF6.004 | - | 0-400 mbarg | STD: 3/4" G (A class) SUBMERSED: 1/2" R (A class) | PVDF \$ PUR \$ FKM \$ Ceramic | Relative Pressure | Ceramic \$ Semi flush | PUR 8 m | 550 |
| HF6.010 | - | 0-1000 mbarg | STD: 3/4" G (A class) SUBMERSED: 1/2" R (A class) | PVDF \$ PUR \$ FKM \$ Ceramic | Relative Pressure | Ceramic \$ Semi flush | PUR 8 m | 550 |
| HF6.100 | - | 0-10 barg | STD: 3/4" G (A class) SUBMERSED: 1/2" R (A class) | PVDF \$ PUR \$ FKM \$ Ceramic | Relative Pressure | Ceramic \$ Semi flush | PUR 8 m | 550 |
| HF6.160 | - | 0-16 barg | STD: 3/4" G (A class) SUBMERSED: 1/2" R (A class) | PVDF \$ PUR \$ FKM \$ Ceramic | Relative Pressure | Ceramic \$ Semi flush | PUR 8 m | 550 |



HF6.XXX

- APPLICATIONS β' Storage Tank management β' Liquid inventory control β' Over flow detection β' Water/Wastewater monitoring β' Chemicals processing β' Tank farm management β' Water recycling MAIN FEATURES β' Level/Pressure/Depth measurement provided by the same transmitter β' Level measurement not affected by foam or vapour β' Premium combination of wetted materials β' Semi flush ceramic diaphragm for a long-lasting operating time β' Options for gauge pressure and for absolute pressure β' Flexible submersible installation (with or without conduit) β' Other operating ranges available on request: full scale @ 600mbar, 1600mbar, 2500mbar, 4000mbar, 6000mbar, 25bar, 40bar (gauge or absolute mode).