

# C300

SS Body and Electrodes Conductivity Sensors with Temperature Sensor (Pt1000) included



Κωδικός προϊόντος	tooltiplmage	Description	Flow Rate Range	Cell Constant	Connection	Installation	Weight (gr.)
C300.001.TCCK	-	Simplified Cell constant	0.55 [CS:Simbolo:μ]S/cm to 200 [CS:Simbolo:μ]S/cm (18,2M[CS:Simbolo:Ω] to 5K[CS:Simbolo:Ω] *cm)	0,01	3 m	EG12SS	150
C300.001TC	-	-	0.55 [CS:Simbolo:μ]S/cm to 200 [CS:Simbolo:μ]S/cm (18,2M[CS:Simbolo:Ω] to 5K[CS:Simbolo:Ω] *cm)	0,01	3 m	EG50P, \$ EG75P, \$ EG12SS	150
C300.10TC	-	-	10 [CS:Simbolo:μ]S/cm to 200000 [CS:Simbolo:μ]S/cm	10	3 m	EG50P, \$ EG75P, \$ EG12SS	150



## C300

- APPLICATIONS β' Agriculture and fertilizing system β' Water treatment β' Foods industry β' Aquaculture β' Ultrapure water application: production and use MAIN FEATURES β' Stainless steel measuring surfaces β' Considerable ratio performance/price β' Temperature sensor included β' Wide range of cell constant β' Rugged sensor body in PP (C100) β' Sensor in SS completely (C300) β' C300.001TCCK with certified cell constant