

## F6.30.XX

Paddlewheel Flow Transmitter



Κωδικός Προϊόντος	tooltiplmage	Version	Power supply	Lenght	Main Wetted Materials	Enclosure	Flow Rate Range	Weight (gr.)
F6.30.01	-	Hall	12 - 24 VCC	L0	C-PVC \$ EPDM	IP65	From 0,15 to 8 m/s*	750
F6.30.02	-	Hall	12 - 24 VCC	L0	C-PVC \$ FKM	IP65	From 0,15 to 8 m/s*	750
F6.30.03	-	Hall	12 - 24 VCC	L1	C-PVC \$ EPDM	IP65	From 0,15 to 8 m/s*	800
F6.30.04	-	Hall	12 - 24 VCC	L1	C-PVC \$ FKM	IP65	From 0,15 to 8 m/s*	800
F6.30.05	-	Hall	12 - 24 VCC	L0	PVDF \$ EPDM	IP65	From 0,15 to 8 m/s*	750
F6.30.06	-	Hall	12 - 24 VCC	L0	PVDF \$ FKM	IP65	From 0,15 to 8 m/s*	750
F6.30.07	-	Hall	12 - 24 VCC	L1	PVDF \$ EPDM	IP65	From 0,15 to 8 m/s*	800
F6.30.08	-	Hall	12 - 24 VCC	L1	PVDF \$ FKM	IP65	From 0,15 to 8 m/s*	800
F6.30.09	-	Hall	12 - 24 VCC	L0	316L SS \$ EPDM	IP65	From 0,15 to 8 m/s*	950
F6.30.10	-	Hall	12 - 24 VCC	L0	316L SS \$ FKM	IP65	From 0,15 to 8 m/s*	950
F6.30.11	-	Hall	12 - 24 VCC	L1	316L SS \$ EPDM	IP65	From 0,15 to 8 m/s*	1000
F6.30.12	-	Hall	12 - 24 VCC	L1	316L SS \$ FKM	IP65	From 0,15 to 8 m/s*	1000



## F6.30.XX

- APPLICATIONS β Industrial water and wastewater treatment β Cooling water systems β Swimming pools β Flow control and monitoring β Water treatment β Water regeneration plant β Processing and manufacturing industry β Water distribution MAIN FEATURES β High chemical resistance β Pipe size range: from DN15 (0,5β) to DN600 (24β) β Low pressure drop β Friendly calibration procedure β 4-20 mA, frequency or volumetric pulse output settable by USB β SSR settable as alarm by laptop