

# M9.05.PX – M9.05.WX

Conductivity Monitor and Transmitter



Κωδικός προϊόντος	tootiplmage	Mounting	Power supply	Wire power Technology	Sensor Input	Output	Weight (gr.)
M9.05.P1	-	Panel	12 - 24 VCC	3/4 wire	Conductivity	2*(4-20mA) \$ 2*(S.S.R.) \$ 2* (mech. relay)	550
M9.05.W1	-	Wall	12 - 24 VCC	3/4 wire	Conductivity	2*(4-20mA) \$ 2*(S.S.R.) \$ 2* (mech. relay)	650
M9.05.W2	-	Wall	110 - 230 VCA	3/4 wire	Conductivity	2*(4-20mA) \$ 2*(S.S.R.) \$ 2* (mech. relay)	750



## M9.05.PX – M9.05.WX

- APPLICATIONS β' Water treatment and regeneration β' Industrial waste water treatment and recovery β' Softener process β' Filtration systems β' Desalination process β' Demineralized water production β' Reverse osmosis/EDI process β' Cooling water monitoring β' Processing and manufacturing industry β' Chemical production MAIN FEATURES β' Wide full graphic display β' Multicolor backlight visualization β' Help on board β' UPW temperature compensation β' Cell constant settable freely β' Values in conductivity, resistivity, TDS β' Analog output for temperature remoting β' Mechanical relay for external device control β' Solid State Relays for programmable alarms β' USB port for software upgrading