

## M9.03.PX – M9.03.WX

Dual Flow Monitor and Transmitter



Κωδικός προϊόντος	tooltiplmage	Mounting	Power supply	Wire power Technology	Sensor Input	Output	Weight (gr.)
M9.03.P1	-	Panel	12 - 24 VCC	3/4 wire	2* Flow (Frequency)	2*(4-20mA) \$ 2*(S.S.R.) \$ 2* (mech. relay)	550
M9.03.W1	-	Wall	12 - 24 VCC	3/4 wire	2* Flow (Frequency)	2*(4-20mA) \$ 2*(S.S.R.) \$ 2* (mech. relay)	650
M9.03.W2	-	Wall	110 - 230 VCA	3/4 wire	2* Flow (Frequency)	2*(4-20mA) \$ 2*(S.S.R.) \$ 2* (mech. relay)	750



## M9.03.PX – M9.03.WX

- APPLICATIONS β' Water treatment systems β' Industrial waste water treatment and recovery β' Water distribution β' Filtration systems β' Swimming pools & SPA β' Irrigation & Fertigation β' Leak detection β' Cooling water monitoring β' Processing and manufacturing industry β' Chemical production MAIN FEATURES β' Wide full graphic display β' Multicolor backlight β' Help on board β' Delta flow rates visualization β' Fast, intuitive and mistake-proof calibration software β' Mechanical relays for external device control β' Solid State Relays for programmable alarms β' Multilanguage menu β' USB port for software upgrading