

# M9.10.PX – M9.10.WX

Dual Analog Monitor and Transmitter



Κωδικός προϊόντος	tootiplmage	Mounting	Power supply	Wire power Technology	Sensor Input	Output	Weight (gr.)
M9.10.P1	-	Panel	12 - 24 VCC	3/4 wire	2* (4-20mA)	2*(4-20mA) \$ 2*(S.S.R.) \$ 2* (mech. relay)	550
M9.10.W1	-	Wall	12 - 24 VCC	3/4 wire	2* (4-20mA)	2*(4-20mA) \$ 2*(S.S.R.) \$ 2* (mech. relay)	650
M9.10.W2	-	Wall	110 - 230 VCA	3/4 wire	2* (4-20mA)	2*(4-20mA) \$ 2*(S.S.R.) \$ 2* (mech. relay)	750



## M9.10.PX – M9.10.WX

- APPLICATIONS β' Industrial waste water treatment β' Civil waste water treatment β' Water treatment processes β' Processing and Manufacturing industry β' Chemical processing β' Industrial environment with electromagnetic interferences MAIN FEATURES β' Wide graphic display β' Multicolor backlight β' Help on board β' Simultaneous visualization of two parameters β' Free setting of engineering unit β' Intuitive calibration procedure β' In line adjustment β' Able to handle active and passive analog signal β' USB port for software upgrading