

# PH2XX

Bulb pH Electrodes with epoxy body



Κωδικός προϊόντος	tooltipImage	Features	Operative Range	Cable***	Connection	Installation	Weight (gr.)
PH200C	-	Singol junction	0-14 pH**	Not required	5m \$ (16,5 ft.) Cable	EG50P \$ EG75P \$ MK150200 \$ MIFV20X05 \$ MIMC20X05	200
PH222CD	-	Double junction	0-14 pH**	CN 653 \$ CN 653 TC1	Twist-lock (BNC)	EG50P \$ EG75P \$ MIFV20X05 \$ MIMC20X05	90
PH222CDTC	-	Double junction with Pt100 included	0-14 pH**	Not required	5m \$ (16,5 ft.) Cable	EG50P \$ EG75P \$ MK150200 \$ MIFV20X05 \$ MIMC20X05	220
PH223CD	-	Double junction for FLS fittings	0-14 pH**	CN 653	Twist-lock (BNC)	F3.SP2.4	100



## PH2XX

- APPLICATIONS β' Water treatment β' Neutralization systems β' Water quality monitoring β' Swimming Pools and spas β' Aquaculture β' Agriculture and fertilizing systems β' Process control MAIN FEATURES β' Epoxy body β' Single or double junction technology β' Large gel reference volume β' Easy and quick installation system β' Outline cable or BNC connection β' Version with temperature sensor combined β' Special versions on request β' Low cost fittings