

Stroke limiter with position indicator



Reference	tooltiplmage	system	Category	family	To be used with:	DN
-	-	Special parts and accessories	Accessories for actuated valves	Accessories for pneumatic diaphragm valves	**VM / NO - DA	80 ÷ 100
ZLI001	-	Special parts and accessories	Accessories for actuated valves	Accessories for pneumatic diaphragm valves	DK / NC	15 ÷ 32
ZLI002	-	Special parts and accessories	Accessories for actuated valves	Accessories for pneumatic diaphragm valves	DK / NO - DA	15 ÷ 32
ZLI003	-	Special parts and accessories	Accessories for actuated valves	Accessories for pneumatic diaphragm valves	DKM / NC	40
ZLI004	-	Special parts and accessories	Accessories for actuated valves	Accessories for pneumatic diaphragm valves	DKM / NC	50 ÷ 65
ZLI005	-	Special parts and accessories	Accessories for actuated valves	Accessories for pneumatic diaphragm valves	DKM / NO - DA	40 ÷ 65
ZLI006	-	Special parts and accessories	Accessories for actuated valves	Accessories for pneumatic diaphragm valves	DKP / NC	25 ÷ 40
ZLI007	-	Special parts and accessories	Accessories for actuated valves	Accessories for pneumatic diaphragm valves	DKP / NC	50 ÷ 65
ZLI008	-	Special parts and accessories	Accessories for actuated valves	Accessories for pneumatic diaphragm valves	DKP / NO - DA	25 ÷ 40
ZLI009	-	Special parts and accessories	Accessories for actuated valves	Accessories for pneumatic diaphragm valves	DKP / NO - DA	50 ÷ 65
ZLI010	-	Special parts and accessories	Accessories for actuated valves	Accessories for pneumatic diaphragm valves	CM / CP	12 ÷ 15
ZLI103	-	Special parts and accessories	Accessories for actuated valves	Accessories for pneumatic diaphragm valves	-	-

Stroke limiter with position indicator

- Upper part (PVC-U)
 - Bottom part (PVC-U)
 - Bolts (zinc plated steel)
 - Nuts (zinc plated steel)
 - Gasket (NBR)
 - Reinforcing ring (Stainless steel)
- The reinforcing bush are used to reinforce the pipe PE100 (SDR11) e PE-X, to elong the lifetime of the pipeline and to reduce the collapse risk of the pipe in disadvantages conditions. They use is particularly suggested using PE-X pipes. The two tightening keys (d.16-63 and d.75-110) are important tools to install the **MAGNUM 3G** fittings