


FKOF/LM /SF – Butterfly valve DN 40:400

Hand operated butterfly valve.



Reference	tooltiplmage	Other description	system	Category	family	series	d – Size	DN	PN	A min	A max	B[5:2]	B[5:3]	C	C[5:1]	H
FKOFLM050FOSF	-	Nota: per d75÷225 e 2" 1/2÷8" sono disponibili guarnizioni primarie in NBR	PVDF system	Manual valves	Butterfly valves	FK DN 40÷400	50 – 1"1/2	40	16	99	109	60	137	175	100	1
FKOFLM063FOSF	-	Nota: per d75÷225 e 2" 1/2÷8" sono disponibili guarnizioni primarie in NBR	PVDF system	Manual valves	Butterfly valves	FK DN 40÷400	63 – 2"	50	16	115	125,5	70	143	175	100	1
FKOFLM075FOSF	-	Nota: per d75÷225 e 2" 1/2÷8" sono disponibili guarnizioni primarie in NBR	PVDF system	Manual valves	Butterfly valves	FK DN 40÷400	75 – 2"1/2	65	10	128	144	80	164	175	110	1
FKOFLM090FOSF	-	Nota: per d75÷225 e 2" 1/2÷8" sono	PVDF system	Manual valves	Butterfly valves	FK DN 40÷400	90 – 3"	80	10	145	160	93	178	175	100	1



FKOF/LM /SF - Butterfly valve DN 40:400

Reference	tooltipImage	Other description	system	Category	family	series	d - Size	DN	PN	A min	A max	B[5:2]	B[5:3]	C	C[5:1]	H
		disponibili guarnizioni primarie in NBR														
FKOFLM110F0SF	-	Nota: per d75÷225 e 2" 1/2÷8" sono disponibili guarnizioni primarie in NBR	PVDF system	Manual valves	Butterfly valves	FK DN 40÷400	110 - 4"	100	10	165	190	107	192	272	110	2
FKOFLM140F0SF	-	Nota: per d75÷225 e 2" 1/2÷8" sono disponibili guarnizioni primarie in NBR	PVDF system	Manual valves	Butterfly valves	FK DN 40÷400	140 - 5"	125	10	204	215	120	212	330	110	2
FKOFLM160F0SF	-	Nota: per d75÷225 e 2" 1/2÷8" sono disponibili guarnizioni primarie in NBR	PVDF system	Manual valves	Butterfly valves	FK DN 40÷400	160 - 6"	150	10	230	242	134	225	330	110	2



FKOF/LM /SF – Butterfly valve DN 40:400

- **Ergonomic handle** in HIPVC equipped with **locking and unlocking device, release, quick operation and graduated adjustment** in 10 intermediate positions (DN 40÷200). The operating range, starting from the first few degrees of valve opening, also guarantees extremely low pressure drops
- **Customisable Labelling System:** integrated module in the handle, made of a transparent protection plug and a customisable tag holder using the LSE set (available as an accessory). The **customisation** lets you **identify the valve on the system** according to specific needs
- **STAINLESS steel square section stem** completely isolated from the fluid complying with standard ISO 5211:
 - DN 40÷65: 11 mm
 - DN 80÷100: 14 mm
 - DN 125÷150: 17 mm
 - DN 200: 22 mm
 - DN 250÷400: 27 mm
- **Body** in polypropylene based **compound reinforced with fibreglass (PP-GR) resistant to UV rays** and characterised by **high mechanical strength**
- **Drilling pattern using oval slots** that allow coupling to flanges according to numerous international standards. The special **self-centring inserts in ABS** supplied for DN 40÷200 guarantee the **correct axial alignment** of the valve during installation. For DN 250÷400 valves, the drilling pattern for the selfcentring system is of the traditional type according to DIN and ANSI standards
- **Interchangeable liner** with the dual function of forming a hydraulic seal and isolating the body from the fluid
- Interchangeable Disk in PVDF with through shaft, available in different thermoplastic materials: PVC-U, PP-H, PVC-C, ABS
- Overall dimensions of the valve in accordance with standard ISO 5752 (DN 40÷200 Medium Series 25, DN 250÷300 Long Series 16) and DIN 3202 K2 and ISO 5752 (DN 65÷200 K2, DN 250÷300 K3)
- Can also be installed as an end line valve, bottom discharge valve or tank dump valve
- **Special Lug version** PN 10 fully drilled according to DIN 2501 or ANSI B16.5 cl.150 **with molded-in AISI 316 stainless steel threaded inserts**
- Possibility of installing a manual reducer or pneumatic and/or electric actuators by applying an ISO standard drilling PP-GR flanges. DN 40 ÷ 200 valve equipped with plate with rack in PP-GR. For actuated versions with flange drilled according to ISO 5211 F05, F07, F10. DN 250÷300 valve, fitted with one-piece top flange in high mechanical strength PP-GR with mounting flange for internal components drilled according to standard ISO 5211 F10 (excluding DN 350÷400), F12, F14
- Possibility to have handle with integrated LSQT limit micro switch, even as a retrofit in existing installations