


## S22IV - 110V AC - true union 2way solenoid valve

2 way solenoid valve with female union ends for solvent welding.

Function: Normally closed. Power supply: 110V AC





#### **EPDM**

Reference	system	Category	family	series	d	DN	Α	В	С	Н	H <sub>1</sub>	L	Z	Е	М	g
S22IV0816E110A	Automation system	Electrically actuated valves	Solenoid valves	S1 DN 4÷8	16	8	34	115	130	99	50	14	71	54	67	1000
S22IV0820E110A	Automation system	Electrically actuated valves	Solenoid valves	S1 DN 4÷8	20	8	34	115	130	103	52	16	71	54	67	1000
S22IV1016E110A	Automation system	Electrically actuated valves	Solenoid valves	S1 DN 4÷8	16	10	34	115	130	99	50	14	71	54	67	1000
S22IV1020E110A	Automation system	Electrically actuated valves	Solenoid valves	S1 DN 4÷8	20	10	34	115	130	103	52	16	71	54	67	1000
S22IV1516E110A	Automation system	Electrically actuated valves	Solenoid valves	S1 DN 4÷8	16	15	34	115	130	99	50	14	71	54	67	1000
S22IV1520E110A	Automation system	Electrically actuated valves	Solenoid valves	S1 DN 4÷8	20	15	34	115	130	103	52	16	71	54	67	1000

### S22IV - 110V AC - true union 2-way solenoid valve

Reference	system	Category	family	series	d	DN	Α	В	С	н	H <sub>1</sub>	L	Z	Е	М	g
S22IV0816F110A	Automation system	Electrically actuated valves	Solenoid valves	S2 DN 8÷15	16	8	34	115	130	99	50	14	71	54	67	1000
S22IV0820F110A	Automation system	Electrically actuated valves	Solenoid valves	S2 DN 8÷15	20	8	34	115	130	103	52	16	71	54	67	1000





# S22IV - 110V AC - true union 2way solenoid valve

Reference	system	Category	family	series	d	DN	Α	В	С	н	H <sub>1</sub>	L	Z	Е	М	g
S22IV1016F110A	Automation system	Electrically actuated valves	Solenoid valves	S2 DN 8÷15	16	10	34	115	130	99	50	14	71	54	67	1000
S22IV1020F110A	Automation system	Electrically actuated valves	Solenoid valves	S2 DN 8÷15	20	10	34	115	130	103	52	16	71	54	67	1000
S22IV1516F110A	Automation system	Electrically actuated valves	Solenoid valves	S2 DN 8÷15	16	15	34	115	130	99	50	14	71	54	67	1000
S22IV1520F110A	Automation system	Electrically actuated valves	Solenoid valves	S2 DN 8÷15	20	15	34	115	130	103	52	16	71	54	67	1000





### S22IV - 110V AC - true union 2way solenoid valve

- Installation flexibility and ease of maintenance: high-performance solenoid electric actuator with internal moving parts designed to exceed 5 million maintenance free operating cycles. Adjustable circular section coil with IP65 protection class.
- DIN 43650 electrical connector supplied as standard: includes LED indicator light and rectifier (in the case of an AC coil).
- Lever shutter in EPDM or FKM and lever in stainless steel.
- Suitable for use with aggressive fluids: no metal component in contact with the fluid or the external environment; all the screws are covered by PE protection plugs.
- · Emergency override
- · 2-Way PVC-U body
- Installation flexibility and ease of maintenance: high-performance solenoid electric actuator designed to exceed 5 million maintenance-free operating cycles
- Adjustable circular section coil with IP65 protection class.
- Integrated override with the possibility of being installed in 3 different positions.
- Lever shutter in EPDM or FKM and lever in stainless steel.
- DIN 43650 electrical connector supplied as standard: includes LED indicator light and rectifier (in the case of an AC coil).

