


# S22LV - 12V DC - true union 2-way solenoid valve

#### 2 way solenoid valve with BS female union ends for solvent welding.

Function: Normally closed. Power supply: 12V DC





### **EPDM**

Reference	system	Category	family	series	d	DN	А	В	С	н	H <sub>1</sub>	L	z	E	М	g
S22LV0838E012C	Automation system	Electrically actuated valves	Solenoid valves	S1 DN 4÷8	3/8"	8	34	115	130	99	50	14	71	54	67	1000
S22LV0812E012C	Automation system	Electrically actuated valves	Solenoid valves	S1 DN 4÷8	1/2"	8	34	115	130	104	52	16,5	71	54	67	1000
S22LV1038E012C	Automation system	Electrically actuated valves	Solenoid valves	S1 DN 4÷8	3/8"	10	34	115	130	99	50	14	71	54	67	1000
S22LV1012E012C	Automation system	Electrically actuated valves	Solenoid valves	S1 DN 4÷8	1/2"	10	34	115	130	104	52	16,5	71	54	67	1000
S22LV1538E012C	Automation system	Electrically actuated valves	Solenoid valves	S1 DN 4÷8	3/8"	15	34	115	130	99	50	14	71	54	67	1000
S22LV1512E012C	Automation system	Electrically actuated valves	Solenoid valves	S1 DN 4÷8	1/2"	15	34	115	130	104	52	16,5	71	54	67	1000

### S22LV - 12V DC - true union 2-way solenoid valve

Reference	system	Category	family	series	d	DN	А	В	С	н	H <sub>1</sub>	L	z	E	М	g
S22LV0838F012C	Automation system	Electrically actuated valves	Solenoid valves	S2 DN 8÷15	3/8"	8	34	115	130	99	50	14	71	54	67	1000
S22LV0812F012C	Automation system	Electrically actuated valves	Solenoid valves	S2 DN 8÷15	1/2"	8	34	115	130	104	52	16,5	71	54	67	1000



All information subject to change. Further information is available at: +49 621 486-0 | info.de@aliaxis.com | aliaxis.de



## S22LV - 12V DC - true union 2-way solenoid valve

Reference	system	Category	family	series	d	DN	А	В	С	н	H <sub>1</sub>	L	Z	Е	М	g
S22LV1038F012C	Automation system	Electrically actuated valves	Solenoid valves	S2 DN 8÷15	3/8"	10	34	115	130	99	50	14	71	54	67	1000
S22LV1012F012C	Automation system	Electrically actuated valves	Solenoid valves	S2 DN 8÷15	1/2"	10	34	115	130	104	52	16,5	71	54	67	1000
S22LV1538F012C	Automation system	Electrically actuated valves	Solenoid valves	S2 DN 8÷15	3/8"	15	34	115	130	99	50	14	71	54	67	1000
S22LV1512F012C	Automation system	Electrically actuated valves	Solenoid valves	S2 DN 8÷15	1/2"	15	34	115	130	104	52	16,5	71	54	67	1000





## S22LV - 12V DC - true union 2-way solenoid valve

- Installation flexibility and ease of maintenance: high-performance solenoid electric actuator with internal moving parts designed to exceed 5 million maintenance free operating cycles. Adjustable circular section coil with IP65 protection class.
- DIN 43650 electrical connector supplied as standard: includes LED indicator light and rectifier (in the case of an AC coil).
- Lever shutter in EPDM or FKM and lever in stainless steel.
- Suitable for use with aggressive fluids: no metal component in contact with the fluid or the external environment; all the screws are covered by PE protection plugs.
- Emergency override
- 2-Way PVC-U body
- Installation flexibility and ease of maintenance: high-performance solenoid electric actuator designed to exceed 5 million maintenance-free operating cycles
- Adjustable circular section coil with IP65 protection class.
- Integrated override with the possibility of being installed in 3 different positions.
- Lever shutter in EPDM or FKM and lever in stainless steel.
- DIN 43650 electrical connector supplied as standard: includes LED indicator light and rectifier (in the case of an AC coil).