

MUN V2A

Transition fitting HD-PE/V2A with male thread

Transition fitting V2A pipe MUN V2A


- Water
- Maximum pressure: Water 16 bar
- Material: PE 100 and V2A [EN 10278, EN 10088-3 - 1.4305 -X8CrNiS18-9, thread according to EN 10226-1]
- Safety technology

Note:

V2A side is anchored in the PE so that it cannot be rotated.

Self-sealing, patented sealing geometry without elastomeric seal for utilisation in water areas.

Other thread dimensions available on request.



PE 100 SDR 11

Maximum permissible working pressure 16 bar (water)



Reference	d	BX	PU	D	R	L	t	z	h	B	Weight kg
616516	40	20	800	58	1"	123	46	75	30	70	0,460
612727	40	20	800	58	1 1/2"	127	46	78	30	70	0,495
612726	50	15	600	70	1 1/2"	137	53	84	30	80	0,600
612705	63	10	400	84	1 1/2"	137	53	84	35	94	0,865
612899	63	10	400	84	2"	142	53	89	35	94	0,910

Other thread dimensions on request

FRIALEN safety fittings can be fused with SDR11 - SDR17.6 pipes, minimum wall thickness s minimum ≥ 3 mm. Other levels of SDR can be processed on request. Please note the mandatory labels directly on the product.

03.07.24 - 23:20



MUN V2A

Transition fitting HD-PE/V2A with male thread

DVGW test marks issued: DV-7501AU2256 and DV-7501AU2257

MUN V2A

Transition fitting HD-PE/V2A with male thread

Areas of Application

FRIALEN-Transition Fittings MUN-V2A are threaded joints as an adaptor from a metal pipe with internal thread to a HD-PE pipe. Joint on the part of HDPE by FRIALEN-Coupler. The threaded joint is made of stainless steel (Material St. 1.4305 / X8CrNiS18-9).

Assembly Instructions

During assembly, only a spanner applied to the provided metal hexagon must be used to screw the component into its metal counterpart. The fusion of the HD-PE side takes place by FRIALEN-fusing – leakproof and longitudinally strong.

The installation of the stainless steel and the HD-PE side has to be prepared according to the general installation instructions (see "Transition Fittings with threaded connection" in "Assembly Instructions" for "FRIALEN-Safety Fittings for house connections and distribution pipes up to d 225"). This involves removing the oxide skin and cleaning the pipe ends.

Good reasons for using the FRIALEN-Transition Fittings MUN-V2A:

- Compact construction
- HD-PE side with exposed heating element for optimal heat transfer
- Cold zones at the end to prevent the flow of molten material
- No holding clamps required
- Large insertion depth, extra wide fusion zones
- Stainless steel end permanently anchored in the HD-PE and will not distort
- Self sealing patented sealing geometry without elastomer seal
- Additional barcode for tracing back the underground fitting (Traceability-Coding)
- Threaded joint made of stainless steel (St. 1.4305) = resistant to corrosion
- Suitable for usage in high humidity environment or in industrial area