

FRIAMAT print eco

Fusion unit with simple documentation function

Powerful universal fusion unit FRIAMAT print eco

- Documentation function (only fusion data)
- 1,000 fusion protocols
- Output via USB interface
- State-of-the-art toroidal core technology with active cooling.
- Bright colour TFT display
- With mini scanner, reader wand or 1D/2D scanner (2D barcodes according to ISO 12176-5)
- Extra long fusion cable (4 m)
- Extra long power cable (5 m)
- Weight approx. 18.0 kg

Note:

Possibility of updating the FRIAMAT software via the USB interface by the user.



Reference	Article description	BX	Weight kg
611122	With mini scanner	1	18,000
613122	With reader wand	1	18,000
614122	With 1D/2D scanner	1	18,000

Technical data 1)	FRIAMAT print eco 2)
Type of device	Universal fusion unit with documentation function
Model with mini scanner	Order no. 611122
Model with reader wand	Order no. 613122
Model with 1D/2D scanner	Order no. 614122
Maximum diameter	Up to d 1200.3)

FRIAMAT print eco

Fusion unit with simple documentation function

Input voltage section	AC 190 V - 250 V
Frequency range	44 Hz ... 66 Hz
Current consumption	AC 16 A maximum
Power	3.5 kW
Unit fuse	16 A sluggish
Welding tension	8 - 48 V
Output current	maximum 110 A
Welding current monitoring	Short circuit and interruption
Barcode type	1D-Code 2/5 interleaved, 2D-Code (QR; Aztec; Data Matrix) according to ISO 12176-5
Interface	USB
Documentation of fusion data	yes
Documentation of traceability data	no
Data memory	1000 protocols
Log format	PDF
Manual emergency barcode input	yes
FRIAMAT preCHECK function	yes
Software update via USB interface	-
Fusion-Pass	-
Supervisor-Pass	-
Start/stop pass for remote control	optional (order no. 624003)
Working temperature range	-20 °C ... +50 °C
Language variants	23
Connection cable	5 m with contour plug
Fusion cable	4 m with connection plug Ø 4 mm
Weight	approx. 18 kg
Dimensions W x D x H	260 x 500 x 340 mm
Casing	Protection category IP 54 / protection category I
Approval / quality	CE, ISO 9001, WEEE-Reg.-No. DE 49130851, RoHS, REACH
Accessories	Operating instructions, transport box

¹⁾ Subject to technical modifications.

²⁾ From year of construction Q2/2021

³⁾ With the FRIAMAT print eco, FRIALEN and FRIAFIT safety fittings up to d 900 can be fused in the entire working temperature range from -20 °C to +50 °C.

Utilising processing fittings from other manufacturers is possible even up to d 1200 and possibly larger. However, the specific power requirement of the fitting at the prevailing processing temperature must always be clarified beforehand with the fitting manufacturer.

FRIAMAT print eco

Fusion unit with simple documentation function

- High performance due to innovative toroidal transformer technology with flow-optimized, active cooling.
- High-resolution, extremely bright 4.3" TFT color display. Documentation of fusion and traceability data. Memory space for up to 1,000 fusion logs. PDF file output to standard USB stick.
- With mini-scanner, reader wand or new 1D/2D scanner for reading 2D barcodes according to ISO 12176-5. Adapter bag, language selection, adjustable buzzer volume, manual emergency entry. Extra-long power cable (4 m) and extra-long fusion cable (5 m). Weight approx 18 kg.
- Continuous monitoring of the entire fusion process and all device functions.
- With FRIAMAT preCHECK function: The most advanced way to fuse with foresight. The FRIAMAT automatically determines whether the next fusion can be performed completely to the end.
- The user himself can install software updates via USB interface.