

FWAB

Drilling equipment

FWAB drilling equipment for drilling HD-PE pipes in a pressure-free condition:

- FRIALEN spigot saddles SA VL
- FRIALEN spigot saddles SA UNI
- FRIAFIT spigot saddles ASA UNI
- FRIAFIT sewage saddles ASA VL
- Driven by drill

Comprising:

- Hole saw (nominal size-related), hole saw mounting with drill shaft SDS-maximum,
- Extension for hole saw mounting (not for FWAB ASA as well as for SA UNI applications),
- Centring drill with ejector and catch sleeve
- Hexagonal spanner.

Note:

(Fig. shows FWAB 400)



Reference	Article description	BX	Outgoing dimension	Weight kg
613832	FWAB 90 for FRIALEN SA UNI	-	d 90	12,600
613833	FWAB 110 for FRIALEN SA UNI	-	d 110	12,600
613834	FWAB 125 for FRIALEN SA UNI	-	d 125	6,000
613829	FWAB 160 for FRIALEN SA UNI	1	d 160	13,600
613830	FWAB 225 for FRIALEN SA VL	1	d 225	14,300
613831	FWAB 250 for FRIALEN SA VL	1	d 250	12,600
613850	FWAB 280 for FRIALEN SA VL	-	d 280	12,600
613851	FWAB 315 for FRIALEN SA VL	-	d 315	12,600

FWAB

Drilling equipment

Reference	Article description	BX	Outgoing dimension	Weight kg
613852	FWAB 355 for FRIALEN SA VL	-	d 355	14,300
613836	FWAB 400 for FRIALEN SA VL	1	d 400	14,300
613838	FWAB 160 for FRIAFIT ASA UNI	1	d 160	6,000
613816	FWAB ASA 160 for FRIAFIT ASA VL	1	d 160	11,200
613835	FWAB ASA 225 for FRIAFIT ASA VL	1	d 225	13,200