

URFA

Ultra-Range Flange Adaptor


Ultra-Range is the same as MegaFit.

Flange adapter for connecting pipes made of different materials (steel, cast iron, ductile cast iron, asbestos cement, PVC, PE-HD/PEX).

- Housing and follower ring made of ductile cast iron (EN-GS-450-10)
- Rilsan corrosion protection (min. 250 µm according to GSK)
- Screws and nuts galvanized/sheraplex-coated or made of stainless steel
- Seal material EPDM or NBR
- Diameter tolerance max. 34 mm depending on dimensions
- Pipes can be angled by max. 4 degrees
- Flange connection dimensions in accordance with DIN EN1092, PN 10 and PN 16

Note:

When used on PE-HD/PEX pipes, our SHVA inner support sleeve is required. Alternatively, we recommend the longitudinally force-locking product FRIAGRIP.



Nuts and bolts galvanized and sheraplex coated Gasket EPDM, DIN-EN 681-1 / KTW / UBA / DVGW-W270

PFA /PN Water: up to DN 300 = 16 bar, larger DN 300 = 10 bar

Reference	d	DN	Flansch DN	Flansch PN	BX	PU	D	L	t min	t max	Weight kg
UR-14R9-043-05	43,5-63,5	40/50	50	10/16	4	96	167	115	80	90	4,100
UR-14R9-063-06	63,0-83,7	65	65	10/16	4	96	185	120	80	90	4,950
UR-14R9-085-08	85,7-107,0	80	80	10/16	2	60	200	140	80	110	5,850
UR-14R9-107-10	107,2-133,2	100	100	10/16	2	48	234	170	85	110	8,900
UR-14R9-132-12	132,2-160,2	125	125	10/16	2	48	268	150	90	120	10,700

URFA

Ultra-Range Flange Adaptor

Reference	d	DN	Flansch DN	Flansch PN	BX	PU	D	L	t min	t max	Weight kg
UR-14R9-158-15	158,2-192,2	150	150	10/16	1	18	317	200	100	125	14,700
UR-14R9-192-20	192,2-226,9	175	200	10/16	1	18	344	230	100	150	18,000
UR-14R9-218-20	218,1-252,1	200	200	10/16	1	18	374	230	100	150	20,950
UR-14R9-266-25	266,2-300,2	250	250	10/16	1	4	424	285	100	180	32,200
UR-14R9-315-30	315,0-349,0	300	300	10/16	1	4	472	285	100	180	39,200

Nuts and Bolts Stainless steel ,Gasket EPDM, DIN-EN 681-1 / KTW / UBA / DVGW-W270

PFA /PN Water: up to DN 300 = 16 bar, larger DN 300 = 10 bar

Reference	d	DN	Flansch DN	Flansch PN	BX	PU	D	L	t min	t max	Weight kg
UR-14R9X043-05	43,5-63,5	40/50	50	10/16	4	96	167	115	80	90	4,100
UR-14R9X063-06	63,0-83,7	65	65	10/16	4	96	185	120	80	90	4,800
UR-14R9X085-08	85,7-107,0	80	80	10/16	2	60	200	140	80	110	5,830
UR-14R9X107-10	107,2-133,2	100	100	10/16	2	48	234	170	85	110	9,100
UR-14R9X132-12	132,2-160,2	125	125	10/16	2	48	268	150	90	120	10,500
UR-14R9X158-15	158,2-192,2	150	150	10/16	1	18	317	200	100	125	13,500
UR-14R9X192-20	192,2-226,9	175	200	10/16	1	18	344	230	100	150	17,200
UR-14R9X218-20	218,1-252,1	200	200	10/16	1	18	374	230	100	150	22,400
UR-14R9X266-25	266,2-300,2	250	250	10/16	1	4	424	285	100	180	32,800
UR-14R9X315-30	315,0-349,0	300	300	10/16	1	4	472	285	100	180	39,400

Nuts and bolts galvanized and sheraplex coated, Gasket NBR, DIN-EN 682 MOP Gas = 5 bar / other water qualities = 16 bar

Reference	d	DN	Flansch DN	Flansch PN	BX	PU	D	L	t min	t max	Weight kg
UR-14R2-043-05	43,5-63,5	40/50	50	10/16	4	96	167	115	80	90	4,100
UR-14R2-063-06	63,0-83,7	65	65	10/16	4	96	185	120	80	90	4,950
UR-14R2-085-08	85,7-107,0	80	80	10/16	2	60	200	140	80	110	5,850
UR-14R2-107-10	107,2-133,2	100	100	10/16	2	48	234	170	85	110	8,900
UR-14R2-132-12	132,2-160,2	125	125	10/16	2	48	268	150	90	120	10,700
UR-14R2-158-15	158,2-192,2	150	150	10/16	1	18	317	200	100	125	14,700
UR-14R2-192-20	192,2-226,9	175	200	10/16	1	18	344	230	100	150	18,000
UR-14R2-218-20	218,1-252,1	200	200	10/16	1	18	374	230	100	150	20,950
UR-14R2-266-25	266,2-300,2	250	250	10/16	1	4	424	285	100	180	32,200
UR-14R2-315-30	315,0-349,0	300	300	10/16	1	4	472	285	100	180	39,200

URFA

Ultra-Range Flange Adaptor

Nuts and bolts Stainless Steel, Gasket NBR, DIN-EN 682 MOP Gas = 5 bar / other water qualities = 16 bar

Reference	d	DN	Flansch DN	Flansch PN	BX	PU	D	L	t min	t max	Weight kg
UR-14R2X043-05	43,5-63,5	40/50	50	10/16	4	96	167	115	80	90	4,100
UR-14R2X063-06	63,0-83,7	65	65	10/16	4	96	185	120	80	90	4,800
UR-14R2X085-08	85,7-107,0	80	80	10/16	2	60	200	140	80	110	5,830
UR-14R2X107-10	107,2-133,2	100	100	10/16	2	48	234	170	85	110	9,100
UR-14R2X132-12	132,2-160,2	125	125	10/16	2	48	268	150	90	120	10,500
UR-14R2X158-15	158,2-192,2	150	150	10/16	1	18	317	200	100	125	13,500
UR-14R2X192-20	192,2-226,9	175	200	10/16	1	18	344	230	100	150	17,200
UR-14R2X218-20	218,1-252,1	200	200	10/16	1	18	374	230	100	150	22,400
UR-14R2X266-25	266,2-300,2	250	250	10/16	1	4	424	285	100	180	32,800
UR-14R2X315-30	315,0-349,0	300	300	10/16	1	4	472	285	100	180	39,400

URFA

Ultra-Range Flange Adaptor

Application areas

Ultra-Range flange adapters and couplings are flexible connectors for pipes made of steel, cast iron, ductile iron, fiber cement, PVC, PE-HD/PEX, available from DN 40 to DN 300.

The clamping ranges up to DN 300 are designed so that a component can be used on all pipe materials of a nominal diameter.

The flange patterns for URFA are generally designed in PN 10 and PN 16 in accordance with EN 1092.

Ultra-Range can be subjected to operating pressures of up to 16 bar for water and up to PN 5 for gas.

Ultra-Range can be used with NBR gaskets for gas, water and waste water, and with EPDM gaskets (DVGW-W270 [11.2007], KTW) in drinking water distribution networks. Screws and nuts correspond to strength class 8.8/8 and are galvanized/sheraplex-coated or made of stainless steel.

Processing instructions

Ultra-Range can be used to make flexible connections between pipes made of the same or different materials.

The pipe ends must be prepared in accordance with the general installation requirements (see FRIAGRIP installation instructions).

The insertion depths $t_{min.}/t_{max.}$ must be observed.

When using PE-HD/PEX pipes, the FRIAGRIP support sleeve (type FRIATEC Mod. SHVA, see current FRIAGRIP price list) must be used. Alternatively, we recommend the restrained products FRIAGRIP

Good reasons for Ultra-Range

Proven design, body and follower ring made of ductile cast iron GGG40 and coated with RILSAN[®]

Flanges are generally drilled to PN 10 and PN 16

The components are supplied pre-assembled at the factory, so no conversion or replacement work is required on site

One gasket for the pipe materials steel, cast iron, ductile cast iron, fiber cement, PVC, PE-HD/PEX

Pipes can be angled up to 8° (URK) or 4° (URFA). In the event of pipe fractures, a misalignment can be compensated for by installing two couplings. The couplings act like a joint and keep the pipe stress-free

Simple installation with standard tools

One torque for all pipe materials

It is not necessary to check the tightening torque of the screws several times

The tolerance range of up to 34 mm enables different pipe materials to be connected to one component. Reduced stock levels for suppliers and retailers