

Bend 15° S/S

Push-Fit PVC-U Fittings EN 1401
Gaskets EN 681-1 DIN 4060

RAL 8023 Red - RAL 7037 Grey



Reference	tooltiplmage	DN (mm)	S (mm)	Z1 (mm)	Z2 (mm)	L1 (mm)	L2 (mm)	α	RAL	Type	Gasket	Version
010115E	-	110	3,2	9	22	62	50	15°	8023	SN8-SDR34	Standard	-
0101142	-	110	3,2	9	22	62	50	15°	7037	SN8-SDR34	Bloccata/Fixed	-
0101242	-	125	3,2	10	22	68	63	15°	7037	-	Bloccata/Fixed	-
010125E	-	125	3,2	10	22	68	63	15°	8023	-	Standard	-
0101742	-	160	4,7	14	28	82	72	15°	7037	SN8 SDR34	Standard	-
0101642	-	160	4,0	14	28	82	72	15°	7037	-	Bloccata/Fixed	-
010165E	-	160	4,0	14	28	82	72	15°	8023	-	Standard	-
0102042	-	200	4,9	18	35	100	86	15°	7037	-	Bloccata/Fixed	-
010205E	-	200	4,9	18	35	100	86	15°	8023	-	Standard	-
0102552	-	250	6,2	19	40	134	103	15°	7037	-	Standard	-
0102591	-	250	6,2	19	40	134	103	15°	8023	-	Standard	-
0103052	-	315	7,7	23	52	144	120	15°	7037	-	Standard	-
0103091	-	315	7,7	23	52	144	120	15°	8023	-	Standard	-
1104052	-	400	9,8	83	80	175	175	15°	7037	-	Standard	-
1104091	-	400	9,8	83	80	175	175	15°	8023	-	Standard	-
N105091	-	500	12,2	150	160	160	250	15°	8023	Fabricated	Standard	upon request
N106391	-	630	-	-	-	-	-	15°	8023	Fabricated	Standard	upon request