

# Invert reducer

Push-Fit PVC-U Fittings EN 1401  
Gaskets EN 681-1 DIN 4060

RAL 8023 Red - RAL 7037 Grey



Reference	tooltiplmage	DN (mm)	DN1 (mm)	S (mm)	Z (mm)	L1 (mm)	L2 (mm)	RAL	Type	Gasket
0513242	-	110	125	3,2	22	56	63	7037	Eccentric	Bloccata/Fixed
051325E	-	110	125	3,2	22	56	63	8023	Eccentric	Standar
0511642	-	110	160	4,0	43	56	82	7037	Eccentric	Bloccata/Fixed
051165E	-	110	160	4,0	43	56	82	8023	Eccentric	Standard
0513642	-	125	160	4,0	36	62	82	7037	Eccentric	Bloccata/Fixed
051365E	-	125	160	4,0	36	62	82	8023	Eccentric	Standard
0512042	-	125	200	4,9	53	62	100	7037	Eccentric	Bloccata/Fixed
051205E	-	125	200	4,9	53	62	100	8023	Eccentric	Standard
0514042	-	160	200	4,9	39	74	100	7037	Eccentric	Bloccata/Fixed
051405E	-	160	200	4,9	39	74	100	8023	Eccentric	Standard
0514642	-	160	250	6,2	66	73	125	7037	Eccentric	Bloccata/Fixed
0514651	-	160	250	6,2	66	73	125	8023	Eccentric	Standard
0512542	-	200	250	6,2	39	96	134	7037	Eccentric	Bloccata/Fixed
051255E	-	200	250	6,2	39	96	134	8023	Eccentric	Standard
0513342	-	200	315	7,7	85	86	145	7037	Eccentric	Bloccata/Fixed
051335E	-	200	315	7,7	85	86	145	8023	Eccentric	Standard
0513052	-	250	315	7,7	64	103	144	7037	Eccentric	Bloccata/Fixed
0513091	-	250	315	7,7	64	103	144	8023	Eccentric	Standard
0519252	-	315	400	9,8	88	118	156	7037	Eccentric	Bloccata/Fixed
0519291	-	315	400	9,8	88	118	156	8023	Eccentric	Standard

# Invert reducer

Reference	tooltiplmage	DN (mm)	DN1 (mm)	S (mm)	Z (mm)	L1 (mm)	L2 (mm)	RAL	Type	Gasket
D519491	-	400	500	-	-	-	-	8023	CENTREE'	Standard