

Non-tension resistant pipe coupling

STRAUB-OPEN-FLEX-3.5

With joint, slotted casing, 2-part or 3-part, STRAUB-OPEN-FLEX can be mounted easily and quickly on existing pipes. STRAUB-OPEN-FLEX pipe couplings have the same characteristics as STRAUB-FLEX couplings, but expand their possible uses. The casings of the STRAUB-OPENFLEX product series can be hinged or available as 2-part or 3-part version. As a result, STRAUB-OPENFLEX couplings can be used for connecting pipes or repairs without removal of existing pipes.



OPEN-FLEX 3.5 ø 323.9 - 1219.2 mm

adMm	Clamping range [mm]	PN Industry [bar] 25	PN Industry [bar] 6	PN Industry [bar] 10	PN Industry [bar] 16	PN Industry [bar] 20	PN Industry [bar] 2.5
323.9	320 - 327	W1 W5	W1 W5	W1 W5	W1 W5	W1 W5	W1 W5
355.6	352 - 359	W1 W5	W1 W5	W1 W5	W1 W5	W1 W5	W1 W5
406.4	402 - 410	W1 W5	W1 W5	W1 W5	W1 W5	W1 W5	W1 W5
457.2	453 - 461	W1 W5	W1 W5	W1 W5	W1 W5	W1 W5	W1 W5
508	504 - 512	W1 W5	W1 W5	W1 W5	W1 W5	W1 W5	W1 W5
558.8	555 - 563	W1 W5	W1 W5	W1 W5	W1 W5	W1 W5	W5*
609.6	605 - 614	W1 W5	W1 W5	W1 W5	W1 W5	W1 W5	W5*
655	651 - 659	W1 W5	W1 W5	W1 W5	W1 W5	W5*	W5*
711.2	707 - 715	W1 W5	W1 W5	W1 W5	W1 W5	W5*	W5*
762	758 - 766	W1 W5	W1 W5	W1 W5	W1 W5	W5*	W5*
812.8	809 - 817	W1 W5	W1 W5	W1 W5	W1 W5	W5*	W5*
914.4	910 - 918	W1 W5	W1 W5	W1 W5	W5*	W5*	W5*
1016	1011 - 1021	W1 W5	W1 W5	W1 W5	W5*	W5*	-
1117.6	1112 - 1123	W1 W5	W1 W5	W1 W5	W5*	W5*	-
1219.2	1214 - 1224	W1 W5	W1 W5	W1 W5	W5*	-	-

Non-tension resistant pipe coupling

STRAUB-OPEN-FLEX-3.5

adMm	Clamping range [mm]	PN Industry [bar] 25	PN Industry [bar] 6	PN Industry [bar] 10	PN Industry [bar] 16	PN Industry [bar] 20	PN Industry [bar] 2.5
1320.8	1316 - 1325	W1 W5	W1 W5	W1 W5*	W5*	-	-
1422.4	1417 - 1427	W1 W5	W1 W5	W5*	-	-	-
1524	1519 - 1529	W1 W5	W1 W5	W5*	-	-	-
1600	1595 - 1605	W1 W5	W1 W5	W5*	-	-	-
1625	1620 - 1630	W1 W5	W1 W5	W5*	-	-	-
1727.2	1722 - 1732	W1 W5	W1 W5	W5*	-	-	-
1828.8	1824 - 1834	W1 W5	W1 W5	W5*	-	-	-
1930.4	1925 - 1935	W1 W5	W1 W5*	W5*	-	-	-
2032	2026 - 2038	W1 W5	W1 W5*	W5*	-	-	-
2268	2262 - 2274	W1 W5	W1 W5*	-	-	-	-
2540	2534 - 2546	W1 W5	W5*	-	-	-	-
2794	2788 - 2800	W1 W5	W5*	-	-	-	-
3048	3042 - 3054	W1 W5	-	-	-	-	-
3302	3296 - 3308	W1	-	-	-	-	-
3556	3550 - 3562	W1	-	-	-	-	-
3810	3804 - 3816	W1	-	-	-	-	-
4064	4058 - 4070	W1	-	-	-	-	-