


FKOV/RM - Butterfly valve DN 40:400

Gearbox operated butterfly valve.



EPDM

Reference	tooltiplmage	Other description	system	Category	family	series	d	DN	PN	A min	A max	øA	B[5:2]	B[5:5]	B[5:6]	G	G[5:1]
FKOVRM050E	-	Note: for d75÷d225 NBR primary liner available FK suitable for flanged JIS K10 wafer installation is also available on request in the size 10" (DN250), 14" (DN350) and 16" (DN400). * d125, FKOV d140 with special QPV FE-FK d125 for butterfly valve (QPV125FKE) ** d200, FKOV d225 with special	PVC-U system	Manual valves	Butterfly valves	FK DN 40÷400	50	40	16	99	109	-	60	161	133	48	135



FKOV/RM - Butterfly valve DN 40:400

Reference	tooltiplmage	Other description	system	Category	family	series	d	DN	PN	A min	A max	øA	B[5:2]	B[5:5]	B[5:6]	G	G[5:1]
FKOAVRM814E	-	<p>QPV FE-FK d200 for butterfly valve (QPV200FKE) ***ISO-DIN ****ANSI B.16.5 cl.150</p> <p>Note: for d75÷d225 NBR primary liner available FK suitable for flanged JIS K10 wafer installation is also available on request in the size 10" (DN250), 14" (DN350) and 16" (DN400). * d125, FKOV d140 with special QPV FE-FK d125 for butterfly valve (QPV125FKE) ** d200, FKOV d225 with special QPV FE-FK d200 for butterfly valve (QPV200FKE) ***ISO-DIN ****ANSI B.16.5 cl.150</p>	PVC-U system	Manual valves	Butterfly valves	FK DN 40÷400	14"	350	7	-	-	476	280	438	390	88	361
FKOAVRM812E	-	<p>Note: for d75÷d225 NBR primary liner available FK suitable for flanged JIS K10 wafer installation is also available on</p>	PVC-U system	Manual valves	Butterfly valves	FK DN 40÷400	****12"	300	8	-	-	432	245	374	338	88	236





FKOV/RM - Butterfly valve DN 40:400

Reference	tooltiplmage	Other description	system	Category	family	series	d	DN	PN	A min	A max	øA	B[5:2]	B[5:5]	B[5:6]	G	G[5:1]	
		request in the size 10" (DN250), 14" (DN350) and 16" (DN400). * d125, FKOV d140 with special QPV FE-FK d125 for butterfly valve (QPV125FKE) ** d200, FKOV d225 with special QPV FE-FK d200 for butterfly valve (QPV200FKE) ***ISO-DIN ****ANSI B.16.5 cl.150																
FKOAVRM810E	-	Note: for d75÷d225 NBR primary liner available FK suitable for flanged JIS K10 wafer installation is also available on request in the size 10" (DN250), 14" (DN350) and 16" (DN400). * d125, FKOV d140 with special QPV FE-FK d125 for butterfly valve (QPV125FKE) ** d200, FKOV d225 with special QPV FE-FK d200 for butterfly valve	PVC-U system	Manual valves	Butterfly valves	FK DN 40÷400	****10"	250	10	-	-	362	210	317	281	88	236	





FKOV/RM - Butterfly valve DN 40:400

Reference	tooltiplmage	Other description	system	Category	family	series	d	DN	PN	A min	A max	øA	B[5:2]	B[5:5]	B[5:6]	G	G[5:1]
FKOVRM400E	-	<p>(QPV200FKE) ***ISO-DIN ****ANSI B.16.5 cl.150</p> <p>Note: for d75÷d225 NBR primary liner available FK suitable for flanged JIS K10 wafer installation is also available on request in the size 10" (DN250), 14" (DN350) and 16" (DN400). * d125, FKOV d140 with special QPV FE-FK d125 for butterfly valve (QPV125FKE) ** d200, FKOV d225 with special QPV FE-FK d200 for butterfly valve (QPV200FKE) ***ISO-DIN ****ANSI B.16.5 cl.150</p>	PVC-U system	Manual valves	Butterfly valves	FK DN 40÷400	400	400	6	-	-	515	306	438	390	88	361
FKOVRM355E	-	<p>Note: for d75÷d225 NBR primary liner available FK suitable for flanged JIS K10 wafer installation is also available on request in the size 10" (DN250), 14" (DN350)</p>	PVC-U system	Manual valves	Butterfly valves	FK DN 40÷400	355	350	7	-	-	460	280	438	390	88	361





FKOV/RM - Butterfly valve DN 40:400

Reference	tooltiplmage	Other description	system	Category	family	series	d	DN	PN	A min	A max	øA	B[5:2]	B[5:5]	B[5:6]	G	G[5:6]
FKOVRM315E	-	<p>and 16" (DN400). * d125, FKOVR d140 with special QPV FE-FK d125 for butterfly valve (QPV125FKE) ** d200, FKOVR d225 with special QPV FE-FK d200 for butterfly valve (QPV200FKE) ***ISO-DIN ****ANSI B.16.5 cl.150</p> <p>Note: for d75÷d225 NBR primary liner available FK suitable for flanged JIS K10 wafer installation is also available on request in the size 10" (DN250), 14" (DN350) and 16" (DN400). * d125, FKOVR d140 with special QPV FE-FK d125 for butterfly valve (QPV125FKE) ** d200, FKOVR d225 with special QPV FE-FK d200 for butterfly valve (QPV200FKE) ***ISO-DIN ****ANSI B.16.5 cl.150</p>	PVC-U system	Manual valves	Butterfly valves	FK DN 40÷400	***315	300	8	-	-	400	245	374	338	88	236





FKOV/RM - Butterfly valve DN 40:400

Reference	tooltiplmage	Other description	system	Category	family	series	d	DN	PN	A min	A max	øA	B[5:2]	B[5:5]	B[5:6]	G	G[5:1]
FKOVRM280E	-	Note: for d75÷d225 NBR primary liner available FK suitable for flanged JIS K10 wafer installation is also available on request in the size 10" (DN250), 14" (DN350) and 16" (DN400). * d125, FKOV d140 with special QPV FE-FK d125 for butterfly valve (QPV125FKE) ** d200, FKOV d225 with special QPV FE-FK d200 for butterfly valve (QPV200FKE) ***ISO-DIN ****ANSI B.16.5 cl.150	PVC-U system	Manual valves	Butterfly valves	FK DN 40÷400	***280	250	10	-	-	350	210	317	281	88	236
FKOVRM225E	-	Note: for d75÷d225 NBR primary liner available FK suitable for flanged JIS K10 wafer installation is also available on request in the size 10" (DN250), 14" (DN350) and 16" (DN400). * d125, FKOV d140 with special QPV	PVC-U system	Manual valves	Butterfly valves	FK DN 40÷400	225 - 8"	200	10	280	298	-	161	287	256	65	204





FKOV/RM - Butterfly valve DN 40:400

Reference	tootiplmage	Other description	system	Category	family	series	d	DN	PN	A min	A max	øA	B[5:2]	B[5:5]	B[5:6]	G	G[5:1]
FKOVRM160E	-	FE-FK d125 for butterfly valve (QPV125FKE) ** d200, FKOV d225 with special QPV FE-FK d200 for butterfly valve (QPV200FKE) ***ISO-DIN ****ANSI B.16.5 cl.150	PVC-U system	Manual valves	Butterfly valves	FK DN 40÷400	160 - 6"	150	10	230	242	-	134	235	207	48	144
FKOVRM140E	-	Note: for d75÷d225 NBR primary liner available FK suitable for flanged JIS K10 wafer installation is also available on request in the size 10" (DN250), 14" (DN350) and 16" (DN400). * d125, FKOV d140 with special QPV FE-FK d125 for butterfly valve (QPV125FKE) ** d200, FKOV d225 with special QPV FE-FK d200 for butterfly valve (QPV200FKE) ***ISO-DIN ****ANSI B.16.5 cl.150	PVC-U system	Manual valves	Butterfly valves	FK DN 40÷400	140 - 5"	125	10	204	215	-	120	222	194	48	144





FKOV/RM - Butterfly valve DN 40:400

Reference	tooltiplmage	Other description	system	Category	family	series	d	DN	PN	A min	A max	øA	B[5:2]	B[5:5]	B[5:6]	G	G[5:1]
FKOVRM110E	-	<p>available FK suitable for flanged JIS K10 wafer installation is also available on request in the size 10" (DN250), 14" (DN350) and 16" (DN400). * d125, FKOV d140 with special QPV FE-FK d125 for butterfly valve (QPV125FKE) ** d200, FKOV d225 with special QPV FE-FK d200 for butterfly valve (QPV200FKE) ***ISO-DIN ****ANSI B.16.5 cl.150</p> <p>Note: for d75÷d225 NBR primary liner available FK suitable for flanged JIS K10 wafer installation is also available on request in the size 10" (DN250), 14" (DN350) and 16" (DN400). * d125, FKOV d140 with special QPV FE-FK d125 for butterfly valve (QPV125FKE)</p>	PVC-U system	Manual valves	Butterfly valves	FK DN 40÷400	110 - 4"	100	10	165	190	-	107	202	174	48	135





FKOV/RM - Butterfly valve DN 40:400

Reference	tooltiplmage	Other description	system	Category	family	series	d	DN	PN	A min	A max	øA	B[5:2]	B[5:5]	B[5:6]	G	G[5:1]
FKOVRM090E	-	Note: for d75÷d225 NBR primary liner available FK suitable for flanged JIS K10 wafer installation is also available on request in the size 10" (DN250), 14" (DN350) and 16" (DN400). * d125, FKOV d140 with special QPV FE-FK d125 for butterfly valve (QPV125FKE) ** d200, FKOV d225 with special QPV FE-FK d200 for butterfly valve (QPV200FKE) ***ISO-DIN ****ANSI B.16.5 cl.150	PVC-U system	Manual valves	Butterfly valves	FK DN 40÷400	90 - 3"	80	10	145	160	-	93	188	160	48	135
FKOVRM075E	-	Note: for d75÷d225 NBR primary liner available FK suitable for flanged JIS K10 wafer	PVC-U system	Manual valves	Butterfly valves	FK DN 40÷400	75 - 2 1/2"	65	10	128	144	-	80	174	146	48	135





FKOV/RM - Butterfly valve DN 40:400

Reference	tooltiplmage	Other description	system	Category	family	series	d	DN	PN	A min	A max	øA	B[5:2]	B[5:5]	B[5:6]	G	G[5:1]	
		installation is also available on request in the size 10" (DN250), 14" (DN350) and 16" (DN400). * d125, FKOV d140 with special QPV FE-FK d125 for butterfly valve (QPV125FKE) ** d200, FKOV d225 with special QPV FE-FK d200 for butterfly valve (QPV200FKE) ***ISO-DIN ****ANSI B.16.5 cl.150																
FKOVRM063E	-	Note: for d75÷d225 NBR primary liner available FK suitable for flanged JIS K10 wafer installation is also available on request in the size 10" (DN250), 14" (DN350) and 16" (DN400). * d125, FKOV d140 with special QPV FE-FK d125 for butterfly valve (QPV125FKE) ** d200, FKOV d225 with special QPV FE-FK	PVC-U system	Manual valves	Butterfly valves	FK DN 40÷400	63	50	16	115	125,2	-	70	167	139	48	135	





FKOV/RM - Butterfly valve DN 40:400

Reference	tooltiplmage	Other description	system	Category	family	series	d	DN	PN	A min	A max	øA	B[5:2]	B[5:5]	B[5:6]	G	G[5:1]
FKOAVRM816E	-	d200 for butterfly valve (QPV200FKE) ***ISO-DIN ****ANSI B.16.5 cl.150 Note: for d75÷d225 NBR primary liner available FK suitable for flanged JIS K10 wafer installation is also available on request in the size 10" (DN250), 14" (DN350) and 16" (DN400). * d125, FKOV d140 with special QPV FE-FK d125 for butterfly valve (QPV125FKE) ** d200, FKOV d225 with special QPV FE-FK d200 for butterfly valve (QPV200FKE) ***ISO-DIN ****ANSI B.16.5 cl.150	PVC-U system	Manual valves	Butterfly valves	FK DN 40÷400	16"	400	6	-	-	540	306	438	390	88	361

FKM

Reference	tooltiplmage	Other description	system	Category	family	series	d	DN	PN	A min	A max	øA	B[5:2]	B[5:5]	B[5:6]	G	G[5:1]
FKOVRM050F	-	Note: for d75÷d225 NBR primary liner available FK suitable for	PVC-U system	Manual valves	Butterfly valves	FK DN 40÷400	50	40	16	99	109	-	60	161	133	48	135





FKOV/RM - Butterfly valve DN 40:400

Reference	tooltiplmage	Other description	system	Category	family	series	d	DN	PN	A min	A max	øA	B[5:2]	B[5:5]	B[5:6]	G	G[5:1]
FKOAVRM814F	-	<p>flanged JIS K10 wafer installation is also available on request in the size 10" (DN250), 14" (DN350) and 16" (DN400). * d125, FKOV d140 with special QPV FE-FK d125 for butterfly valve (QPV125FKE) ** d200, FKOV d225 with special QPV FE-FK d200 for butterfly valve (QPV200FKE) ***ISO-DIN ****ANSI B.16.5 cl.150</p> <p>Note: for d75÷d225 NBR primary liner available FK suitable for flanged JIS K10 wafer installation is also available on request in the size 10" (DN250), 14" (DN350) and 16" (DN400). * d125, FKOV d140 with special QPV FE-FK d125 for butterfly valve (QPV125FKE) ** d200, FKOV d225</p>	PVC-U system	Manual valves	Butterfly valves	FK DN 40÷400	14"	350	7	-	-	476	280	438	390	88	361





FKOV/RM - Butterfly valve DN 40:400

Reference	tooltiplmage	Other description	system	Category	family	series	d	DN	PN	A min	A max	øA	B[5:2]	B[5:5]	B[5:6]	G	G[5:1]
FKOAVRM812F	-	with special QPV FE-FK d200 for butterfly valve (QPV200FKE) ***ISO-DIN ****ANSI B.16.5 cl.150 Note: for d75÷d225 NBR primary liner available FK suitable for flanged JIS K10 wafer installation is also available on request in the size 10" (DN250), 14" (DN350) and 16" (DN400). * d125, FKOV d140 with special QPV FE-FK d125 for butterfly valve (QPV125FKE) ** d200, FKOV d225 with special QPV FE-FK d200 for butterfly valve (QPV200FKE) ***ISO-DIN ****ANSI B.16.5 cl.150	PVC-U system	Manual valves	Butterfly valves	FK DN 40÷400	****12"	300	8	-	-	432	245	374	338	88	236
FKOAVRM810F	-	Note: for d75÷d225 NBR primary liner available FK suitable for flanged JIS K10 wafer installation is also	PVC-U system	Manual valves	Butterfly valves	FK DN 40÷400	****10"	250	10	-	-	362	210	317	281	88	236





FKOV/RM - Butterfly valve DN 40:400

Reference	tooltiplmage	Other description	system	Category	family	series	d	DN	PN	A min	A max	øA	B[5:2]	B[5:5]	B[5:6]	G	G[5:1]
FKOVRM400F	-	<p>available on request in the size 10" (DN250), 14" (DN350) and 16" (DN400). * d125, FKOV d140 with special QPV FE-FK d125 for butterfly valve (QPV125FKE) ** d200, FKOV d225 with special QPV FE-FK d200 for butterfly valve (QPV200FKE) ***ISO-DIN ****ANSI B.16.5 cl.150</p> <p>Note: for d75÷d225 NBR primary liner available FK suitable for flanged JIS K10 wafer installation is also available on request in the size 10" (DN250), 14" (DN350) and 16" (DN400). * d125, FKOV d140 with special QPV FE-FK d125 for butterfly valve (QPV125FKE) ** d200, FKOV d225 with special QPV FE-FK d200 for butterfly</p>	PVC-U system	Manual valves	Butterfly valves	FK DN 40÷400	400	400	6	-	-	515	306	438	390	88	361





FKOV/RM - Butterfly valve DN 40:400

Reference	tooltiplmage	Other description	system	Category	family	series	d	DN	PN	A min	A max	øA	B[5:2]	B[5:5]	B[5:6]	G	G[5:1]
FKOVRM355F	-	valve (QPV200FKE) ***ISO-DIN ****ANSI B.16.5 cl.150 Note: for d75÷d225 NBR primary liner available FK suitable for flanged JIS K10 wafer installation is also available on request in the size 10" (DN250), 14" (DN350) and 16" (DN400). * d125, FKOV d140 with special QPV FE-FK d125 for butterfly valve (QPV125FKE) ** d200, FKOV d225 with special QPV FE-FK d200 for butterfly valve (QPV200FKE) ***ISO-DIN ****ANSI B.16.5 cl.150	PVC-U system	Manual valves	Butterfly valves	FK DN 40÷400	355	350	7	-	-	460	280	438	390	88	361
FKOVRM315F	-	Note: for d75÷d225 NBR primary liner available FK suitable for flanged JIS K10 wafer installation is also available on request in the size 10" (DN250),	PVC-U system	Manual valves	Butterfly valves	FK DN 40÷400	***315	300	8	-	-	400	245	374	338	88	236





FKOV/RM - Butterfly valve DN 40:400

Reference	tooltiplmage	Other description	system	Category	family	series	d	DN	PN	A min	A max	øA	B[5:2]	B[5:5]	B[5:6]	G	G[5:1]
FKOVRM280F	-	<p>14" (DN350) and 16" (DN400). * d125, FKOV d140 with special QPV FE-FK d125 for butterfly valve (QPV125FKE) ** d200, FKOV d225 with special QPV FE-FK d200 for butterfly valve (QPV200FKE) ***ISO-DIN ****ANSI B.16.5 cl.150</p> <p>Note: for d75÷d225 NBR primary liner available FK suitable for flanged JIS K10 wafer installation is also available on request in the size 10" (DN250), 14" (DN350) and 16" (DN400). * d125, FKOV d140 with special QPV FE-FK d125 for butterfly valve (QPV125FKE) ** d200, FKOV d225 with special QPV FE-FK d200 for butterfly valve (QPV200FKE) ***ISO-DIN</p>	PVC-U system	Manual valves	Butterfly valves	FK DN 40÷400	***280	250	10	-	-	350	210	317	281	88	236





FKOV/RM - Butterfly valve DN 40:400

Reference	tooltiplmage	Other description	system	Category	family	series	d	DN	PN	A min	A max	øA	B[5:2]	B[5:5]	B[5:6]	G	G[5:1]
FKOVRM225F	-	<p>****ANSI B.16.5 cl.150</p> <p>Note: for d75÷d225 NBR primary liner available FK suitable for flanged JIS K10 wafer installation is also available on request in the size 10" (DN250), 14" (DN350) and 16" (DN400). * d125, FKOV d140 with special QPV FE-FK d125 for butterfly valve (QPV125FKE) ** d200, FKOV d225 with special QPV FE-FK d200 for butterfly valve (QPV200FKE) ***ISO-DIN ****ANSI B.16.5 cl.150</p>	PVC-U system	Manual valves	Butterfly valves	FK DN 40÷400	225 - 8"	200	10	280	298	-	161	287	256	65	204
FKOVRM160F	-	<p>Note: for d75÷d225 NBR primary liner available FK suitable for flanged JIS K10 wafer installation is also available on request in the size 10" (DN250), 14" (DN350) and 16" (DN400).</p>	PVC-U system	Manual valves	Butterfly valves	FK DN 40÷400	160 - 6"	150	10	230	242	-	134	235	207	48	144





FKOV/RM - Butterfly valve DN 40:400

Reference	tooltiplmage	Other description	system	Category	family	series	d	DN	PN	A min	A max	øA	B[5:2]	B[5:5]	B[5:6]	G	G[5:1]
FKOVRM140F	-	<p>* d125, FKOV d140 with special QPV FE-FK d125 for butterfly valve (QPV125FKE)</p> <p>** d200, FKOV d225 with special QPV FE-FK d200 for butterfly valve (QPV200FKE)</p> <p>***ISO-DIN</p> <p>****ANSI</p> <p>B.16.5 cl.150</p> <p>Note: for d75÷d225 NBR primary liner available FK suitable for flanged JIS K10 wafer installation is also available on request in the size 10" (DN250), 14" (DN350) and 16" (DN400).</p> <p>* d125, FKOV d140 with special QPV FE-FK d125 for butterfly valve (QPV125FKE)</p> <p>** d200, FKOV d225 with special QPV FE-FK d200 for butterfly valve (QPV200FKE)</p> <p>***ISO-DIN</p> <p>****ANSI</p> <p>B.16.5 cl.150</p>	PVC-U system	Manual valves	Butterfly valves	FK DN 40÷400	140 - 5"	125	10	204	215	-	120	222	194	48	144





FKOV/RM - Butterfly valve DN 40:400

Reference	tooltiplmage	Other description	system	Category	family	series	d	DN	PN	A min	A max	øA	B[5:2]	B[5:5]	B[5:6]	G	G[5:1]
FKOVRM110F	-	Note: for d75÷d225 NBR primary liner available FK suitable for flanged JIS K10 wafer installation is also available on request in the size 10" (DN250), 14" (DN350) and 16" (DN400). * d125, FKOV d140 with special QPV FE-FK d125 for butterfly valve (QPV125FKE) ** d200, FKOV d225 with special QPV FE-FK d200 for butterfly valve (QPV200FKE) ***ISO-DIN ****ANSI B.16.5 cl.150	PVC-U system	Manual valves	Butterfly valves	FK DN 40÷400	110 - 4"	100	10	165	190	-	107	202	174	48	135
FKOVRM090F	-	Note: for d75÷d225 NBR primary liner available FK suitable for flanged JIS K10 wafer installation is also available on request in the size 10" (DN250), 14" (DN350) and 16" (DN400). * d125, FKOV d140 with special QPV	PVC-U system	Manual valves	Butterfly valves	FK DN 40÷400	90 - 3"	80	10	145	160	-	93	188	160	48	135





FKOV/RM - Butterfly valve DN 40:400

Reference	tooltiplmage	Other description	system	Category	family	series	d	DN	PN	A min	A max	øA	B[5:2]	B[5:5]	B[5:6]	G	G[5:1]
FKOVRM075F	-	FE-FK d125 for butterfly valve (QPV125FKE) ** d200, FKOVR d225 with special QPV FE-FK d200 for butterfly valve (QPV200FKE) ***ISO-DIN ****ANSI B.16.5 cl.150	PVC-U system	Manual valves	Butterfly valves	FK DN 40÷400	75 - 2"1/2	65	10	128	144	-	80	174	146	48	135
FKOVRM063F	-	Note: for d75÷d225 NBR primary liner available FK suitable for flanged JIS K10 wafer installation is also available on request in the size 10" (DN250), 14" (DN350) and 16" (DN400). * d125, FKOVR d140 with special QPV FE-FK d125 for butterfly valve (QPV125FKE) ** d200, FKOVR d225 with special QPV FE-FK d200 for butterfly valve (QPV200FKE) ***ISO-DIN ****ANSI B.16.5 cl.150	PVC-U system	Manual valves	Butterfly valves	FK DN 40÷400	63	50	16	115	125,2	-	70	167	139	48	135





FKOV/RM - Butterfly valve DN 40:400

Reference	tooltiplmage	Other description	system	Category	family	series	d	DN	PN	A min	A max	øA	B[5:2]	B[5:5]	B[5:6]	G	G[5:1]
FKOAVRM816F	-	<p>available FK suitable for flanged JIS K10 wafer installation is also available on request in the size 10" (DN250), 14" (DN350) and 16" (DN400). * d125, FKOV d140 with special QPV FE-FK d125 for butterfly valve (QPV125FKE) ** d200, FKOV d225 with special QPV FE-FK d200 for butterfly valve (QPV200FKE) ***ISO-DIN ****ANSI B.16.5 cl.150</p> <p>Note: for d75÷d225 NBR primary liner available FK suitable for flanged JIS K10 wafer installation is also available on request in the size 10" (DN250), 14" (DN350) and 16" (DN400). * d125, FKOV d140 with special QPV FE-FK d125 for butterfly valve (QPV125FKE)</p>	PVC-U system	Manual valves	Butterfly valves	FK DN 40÷400	16"	400	6	-	-	540	306	438	390	88	361





FKOV/RM - Butterfly valve DN 40:400

Reference	tooltiplmage	Other description	system	Category	family	series	d	DN	PN	A min	A max	øA	B[5:2]	B[5:5]	B[5:6]	G	G[5:1]
		** d200, FKOV d225 with special QPV FE-FK d200 for butterfly valve (QPV200FKE) ***ISO-DIN ****ANSI B.16.5 cl.150															

FKM

Reference	tooltiplmage	Other description	system	Category	family	series	d	DN	PN	A min	A max	øA	B[5:2]	B[5:5]	B[5:6]	G	G[5:1]
FKOVRM050FOSF	-	Note: for d75÷d225 NBR primary liner available FK suitable for flanged JIS K10 wafer installation is also available on request in the size 10" (DN250), 14" (DN350) and 16" (DN400). * d125, FKOV d140 with special QPV FE-FK d125 for butterfly valve (QPV125FKE) ** d200, FKOV d225 with special QPV FE-FK d200 for butterfly valve (QPV200FKE) ***ISO-DIN ****ANSI B.16.5 cl.150	PVC-U system	Manual valves	Butterfly valves	FK DN 40÷400	50	40	16	99	109	-	60	161	133	48	135
FKOVRM063FOSF	-	Note: for d75÷d225	PVC-U system	Manual valves	Butterfly valves	FK DN 40÷400	63	50	16	115	125,2	-	70	167	139	48	135





FKOV/RM - Butterfly valve DN 40:400

Reference	tooltiplmage	Other description	system	Category	family	series	d	DN	PN	A min	A max	øA	B[5:2]	B[5:5]	B[5:6]	G	G[5:1]
		NBR primary liner available FK suitable for flanged JIS K10 wafer installation is also available on request in the size 10" (DN250), 14" (DN350) and 16" (DN400). * d125, FKOV d140 with special QPV FE-FK d125 for butterfly valve (QPV125FKE) ** d200, FKOV d225 with special QPV FE-FK d200 for butterfly valve (QPV200FKE) ***ISO-DIN ****ANSI B.16.5 cl.150															
FKOVRM075FOSF	-	Note: for d75÷d225 NBR primary liner available FK suitable for flanged JIS K10 wafer installation is also available on request in the size 10" (DN250), 14" (DN350) and 16" (DN400). * d125, FKOV d140 with special QPV FE-FK d125 for butterfly	PVC-U system	Manual valves	Butterfly valves	FK DN 40÷400	75 - 2"1/2	65	10	128	144	-	80	174	146	48	135





FKOV/RM - Butterfly valve DN 40:400

Reference	tooltiplmage	Other description	system	Category	family	series	d	DN	PN	A min	A max	øA	B[5:2]	B[5:5]	B[5:6]	G	G[5:1]
FKOVRM090F0SF	-	valve (QPV125FKE) ** d200, FKOV d225 with special QPV FE-FK d200 for butterfly valve (QPV200FKE) ***ISO-DIN ****ANSI B.16.5 cl.150	PVC-U system	Manual valves	Butterfly valves	FK DN 40÷400	90 - 3"	80	10	145	160	-	93	188	160	48	135
FKOVRM110F0SF	-	Note: for d75÷d225 NBR primary liner available FK suitable for flanged JIS K10 wafer installation is also available on request in the size 10" (DN250), 14" (DN350) and 16" (DN400). * d125, FKOV d140 with special QPV FE-FK d125 for butterfly valve (QPV125FKE) ** d200, FKOV d225 with special QPV FE-FK d200 for butterfly valve (QPV200FKE) ***ISO-DIN ****ANSI B.16.5 cl.150	PVC-U system	Manual valves	Butterfly valves	FK DN 40÷400	110 - 4"	100	10	165	190	-	107	202	174	48	135





FKOV/RM - Butterfly valve DN 40:400

Reference	tooltiplmage	Other description	system	Category	family	series	d	DN	PN	A min	A max	øA	B[5:2]	B[5:5]	B[5:6]	G	G[5:1]
FKOVRM140F0SF	-	<p>flanged JIS K10 wafer installation is also available on request in the size 10" (DN250), 14" (DN350) and 16" (DN400). * d125, FKOV d140 with special QPV FE-FK d125 for butterfly valve (QPV125FKE) ** d200, FKOV d225 with special QPV FE-FK d200 for butterfly valve (QPV200FKE) ***ISO-DIN ****ANSI B.16.5 cl.150</p> <p>Note: for d75÷d225 NBR primary liner available FK suitable for flanged JIS K10 wafer installation is also available on request in the size 10" (DN250), 14" (DN350) and 16" (DN400). * d125, FKOV d140 with special QPV FE-FK d125 for butterfly valve (QPV125FKE) ** d200, FKOV d225</p>	PVC-U system	Manual valves	Butterfly valves	FK DN 40÷400	140 - 5"	125	10	204	215	-	120	222	194	48	144





FKOV/RM - Butterfly valve DN 40:400

Reference	tooltiplmage	Other description	system	Category	family	series	d	DN	PN	A min	A max	øA	B[5:2]	B[5:5]	B[5:6]	G	G[5:1]
FKOVRM160F0SF	-	<p>with special QPV FE-FK d200 for butterfly valve (QPV200FKE) ***ISO-DIN ****ANSI B.16.5 cl.150</p> <p>Note: for d75÷d225 NBR primary liner available FK suitable for flanged JIS K10 wafer installation is also available on request in the size 10" (DN250), 14" (DN350) and 16" (DN400). * d125, FKOV d140 with special QPV FE-FK d125 for butterfly valve (QPV125FKE) ** d200, FKOV d225 with special QPV FE-FK d200 for butterfly valve (QPV200FKE) ***ISO-DIN ****ANSI B.16.5 cl.150</p>	PVC-U system	Manual valves	Butterfly valves	FK DN 40÷400	160 - 6"	150	10	230	242	-	134	235	207	48	144



FKOV/RM – Butterfly valve DN 40:400

- **Ergonomic handle** in HIPVC equipped with **locking and unlocking device, release, quick operation and graduated adjustment** in 10 intermediate positions (DN 40÷200). The operating range, starting from the first few degrees of valve opening, also guarantees extremely low pressure drops.
- **Customisable Labelling System:** integrated module in the handle, made of a transparent protection plug and a customisable tag holder using the LSE set (available as an accessory). The **customisation** lets you **identify the valve on the system** according to specific needs.
- **STAINLESS steel square section stem** completely isolated from the fluid complying with standard ISO 5211:
 - DN 40÷65: 11 mm
 - DN 80÷100: 14 mm
 - DN 125÷150: 17 mm
 - DN 200: 22 mm
 - DN 250÷400: 27 mm
- **Body** in polypropylene based **compound reinforced with fibreglass (PP-GR) resistant to UV rays** and characterised by **high mechanical strength**.
- **Drilling pattern using oval slots** that allow coupling to flanges according to numerous international standards. The special **self-centring inserts in ABS** supplied for DN 40÷200 guarantee the **correct axial alignment** of the valve during installation. For DN 250÷400 valves, the drilling pattern for the selfcentring system is of the traditional type according to DIN and ANSI standards.
- **Interchangeable liner** with the dual function of forming a hydraulic seal and isolating the body from the fluid.
- Interchangeable disk in PVC-U with through shaft, available in different thermoplastic materials: PP-H, PVC-C, ABS, PVDF
- Overall dimensions of the valve in accordance with standard ISO 5752 (DN 40÷200 Medium Series 25, DN 250÷ 300 Long Series 16) and DIN 3202 K2 and ISO 5752 (DN 65÷200 K2, DN 250÷300 K3)
- Can also be installed as an end line valve, bottom discharge valve or tank dump valve
- **Special Lug version** PN 10 fully drilled to DIN 2501 or ANSI B16.5 cl.150 with **molded-in AISI 316 STAINLESS steel threaded inserts**
- **Valve material compatibility** (PVC-U + EPDM) with water conveyance, drinking water and other food substances according to **current regulations**
- Possibility of installing a manual reducer or pneumatic and/or electric actuators by applying an ISO standard drilling PP-GR flanges. DN 40 ÷ 200 valve fitted with plate with rack in PP-GR. For actuated versions with flange drilled according to ISO 5211 F05, 07, F10. DN 250÷400 valve, fitted with one-piece top flange in high mechanical strength PP-GR with mounting flange for internal components drilled according to standard ISO 5211 F10 (excluding DN 350÷400), F12, F14.
- Possibility to have handle with integrated LSQT limit micro switch, even as a retrofit in existing installations