

C300 - Conductivity Sensor

SS body and electrodes conductivity sensors with temperature sensor (Pt1000) included.



Reference	tooltiplmage	system	Category	family	series	Description	Flow Rate Range	Cell Constant	Connectio
C300.001.TCCK	-	Automation system	FLS Measurement and control Instrumentation	ph / ORP / Conductivity Electrodes	Potentiometric and Inductive Conductivity Sensors	Simplified Cell constant	0,055 uS/cm to 200 µS/cm (18,2MΩ*cm to 5KΩ*cm)	0,01	3 m
C300.001TC	-	Automation system	FLS Measurement and control Instrumentation	ph / ORP / Conductivity Electrodes	Potentiometric and Inductive Conductivity Sensors	-	0,055 µS/cm to 200 µS/cm (18,2MΩ*cm to 5KΩ*cm)	0,01	3 m
C300.10TC	-	Automation system	FLS Measurement and control Instrumentation	ph / ORP / Conductivity Electrodes	Potentiometric and Inductive Conductivity Sensors	-	10 µS/cm to 200000 µS/cm	10	3 m

C300 – Conductivity Sensor

APPLICATIONS:

- Agriculture and fertilizing system
- Water treatment
- Foods industry
- Aquaculture
- Ultrapure water application: production and use

MAIN FEATURES:

- Stainless steel measuring surfaces
- Considerable ratio performance/price
- Temperature sensor included
- Wide range of cell constant
- Rugged sensor body in PP (C100)
- Sensor in SS completely (C300)
- C300.001TCCK with certified cell constant