

# M9.10.PX – M9.10.WX

Dual Analog Monitor and Transmitter



Reference	tooltipImage	system	Category	family	series	Mounting	Power supply	Wire power Technology	Sensor Input	Output
M9.10.P1	-	Automation system	FLS Measurement and control Instrumentation	Monitors and transmitters	Monitors for Flow, pH/ ORP, Conductivity measurement and control	Panel	12 – 24 VCC	3/4 wire	2* (4-20mA)	2*(4-20mA) \$ 2*(S.S.R.) \$ 2* (mech. relay)
M9.10.W1	-	Automation system	FLS Measurement and control Instrumentation	Monitors and transmitters	Monitors for Flow, pH/ ORP, Conductivity measurement and control	Wall	12 – 24 VCC	3/4 wire	2* (4-20mA)	2*(4-20mA) \$ 2*(S.S.R.) \$ 2* (mech. relay)
M9.10.W2	-	Automation system	FLS Measurement and control Instrumentation	Monitors and transmitters	Monitors for Flow, pH/ ORP, Conductivity measurement and control	Wall	110 – 230 VCA	3/4 wire	2* (4-20mA)	2*(4-20mA) \$ 2*(S.S.R.) \$ 2* (mech. relay)

## M9.10.PX – M9.10.WX

### APPLICATIONS:

- Industrial waste water treatment
- Civil waste water treatment
- Water treatment processes
- Processing and Manufacturing industry
- Chemical processing
- Industrial environment with electromagnetic interferences

### MAIN FEATURES:

- Wide graphic display
- Multicolor backlight
- Help on board
- Simultaneous visualization of two parameters
- Free setting of engineering unit
- Intuitive calibration procedure
- In line adjustment
- Able to handle active and passive analog signal
- USB port for software upgrading