

M9.02.PX – M9.02.WX

Flow Monitor and Transmitter



Reference	tooltiplmage	system	Category	family	series	Mounting	Power supply	Wire power Technology	Sensor Input	Output
M9.02.P1	-	Automation system	FLS Measurement and control Instrumentation	Monitors and transmitters	Monitors for Flow, pH/ ORP, Conductivity measurement and control	Panel	12 - 24 VCC	3/4 wire	Flow (Frequency)	1* (4-20 mA). 2* (S.S.R.), 1* (mech. relay)
M9.02.W1	-	Automation system	FLS Measurement and control Instrumentation	Monitors and transmitters	Monitors for Flow, pH/ ORP, Conductivity measurement and control	Wall	12 - 24 VCC	3/4 wire	Flow (Frequency)	1* (4-20 mA) \$ 2* (S.S.R.) \$ 1* (mech. relay)
M9.02.W2	-	Automation system	FLS Measurement and control Instrumentation	Monitors and transmitters	Monitors for Flow, pH/ ORP, Conductivity measurement and control	Wall	110 - 230 VCA	3/4 wire	Flow (Frequency)	1* (4-20 mA) \$ 2* (S.S.R.) \$ 1* (mech. relay)



M9.02.PX – M9.02.WX

APPLICATIONS:

- Water treatment systems
- Industrial waste water treatment and recovery
- Water distribution
- Filtration systems
- Swimming pools & SPA
- Irrigation & Fertigation
- Leak detection
- Cooling water monitoring
- Processing and manufacturing industry
- Chemical production

MAIN FEATURES:

- Wide full graphic display
- Multicolor backlight
- Help on board
- Installation flexibility
- Fast, intuitive and mistake-proof calibration software
- Mechanical relay for external device control
- Solid State Relays for programmable alarms
- Multilanguage menu
- USB port for software upgrading