

Data specific for pH-ORP.200

Bulb ORP Electrodes with epoxy body



Reference	system	Category	family	series	Corpo	Materiale/ tipo di giunzione	Soluzione di riferimento	Superficie di rilevamento	O-ring	Collegame
ORP200C	Automation system	FLS Measurement and control Instrumentation	ph / ORP / Conductivity Electrodes	Bulb and Flat pH/ ORP Electrodes with Epoxy, C-PVC, Ryton or Glass body	resina epossidica	nylon/S.J.	KCl 3,5 M	platino	-	5 m (16,5 p)
ORP222CD	Automation system	FLS Measurement and control Instrumentation	ph / ORP / Conductivity Electrodes	Bulb and Flat pH/ ORP Electrodes with Epoxy, C-PVC, Ryton or Glass body	resina epossidica	nylon/D.J.	KCl 3,5 M / KNO3 sat.	platino	silicone	Twist-Lock (BNC)
ORP223CD	Automation system	FLS Measurement and control Instrumentation	ph / ORP / Conductivity Electrodes	Bulb and Flat pH/ ORP Electrodes with Epoxy, C-PVC,	resina epossidica	nylon/D.J.	KCl 3,5 M / KNO3 sat.	platino	silicone	Twist-Lock (BNC)

Data specific for pH-ORP.200

Reference	system	Category	family	series	Corpo	Materiale/ tipo di giunzione	Soluzione di riferimento	Superficie di rilevamento	O-ring	Collegamento
				Ryton or Glass body						
PH200C	Automation system	FLS Measurement and control Instrumentation	ph / ORP / Conductivity Electrodes	Bulb and Flat pH/ ORP Electrodes with Epoxy, C-PVC, Ryton or Glass body	resina epossidica	nylon/S.J.	KCl 3,5 M	membrana in vetro di pH	-	5 m (16,5 p)
PH222CD	Automation system	FLS Measurement and control Instrumentation	ph / ORP / Conductivity Electrodes	Bulb and Flat pH/ ORP Electrodes with Epoxy, C-PVC, Ryton or Glass body	resina epossidica	nylon/D.J.	KCl 3,5 M / KNO3 sat.	membrana in vetro di pH	silicone	Twist-Lock (BNC)
PH222CDTC	Automation system	FLS Measurement and control Instrumentation	ph / ORP / Conductivity Electrodes	Bulb and Flat pH/ ORP Electrodes with Epoxy, C-PVC, Ryton or Glass body	resina epossidica	nylon/D.J.	KCl 3,5 M / KNO3 sat.	membrana in vetro di pH	-	5 m (16,5 p)
PH223CD	Automation system	FLS Measurement and control Instrumentation	ph / ORP / Conductivity Electrodes	Bulb and Flat pH/ ORP Electrodes with Epoxy, C-PVC, Ryton or Glass body	resina epossidica	nylon/D.J.	KCl 3,5 M / KNO3 sat.	membrana in vetro di pH	silicone	Twist-Lock (BNC)

Data specific for pH-ORP.200

APPLICATIONS:

- Water treatment
- Neutralization systems
- Water quality monitoring
- Swimming Pools and spas
- Aquaculture
- Agriculture and fertilizing systems
- Process control

MAIN FEATURES:

- Epoxy body
- Single or double junction technology
- Large gel reference volume
- Easy and quick installation system
- Outline cable or BNC connection
- Version with temperature sensor combined
- Special versions on request
- Low cost fittings